NOTICE: TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT. L.C.S. within 30 days from the date of well completion.

WATER WELL REPORT FINE VED STATE OF OREGON (Please type or print) OCT - 1 1979 (Do not write above this line) WATER RESOURCES DEPT WATER WELL REPORT FOR State Well No. 1.

12818

(1) OWNER:	(10) LOCATION OF WELL:
Name J.A. Bush	County Lane, Driller's well number
Address 90536 Territorial Rd Junction City	NE 14 NE 14 Section 6 T. 173 R. 5W W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner This /00
New Well M Deepening ☐ Reconditioning ☐ Abandon ☐	11619 / 00
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Planets of males and the second secon
Rotary Driven Domestic D Industrial D Municipal D	Static level 30 ft. below land surface. Date 8-28-79
Bored Irrigation K Test Well Other	
	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
\$300 Diam from + 12 ft. to 44 ft. Gage , 250	Depth drilled 203 ft. Depth of completed well 203 ft.
" Diam. from	Formation: Describe color, texture, grain size and structure of materials;
To the state of th	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
(6) PERFORATIONS: Perforated? ☐ Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Soil 0 2t
perforations from ft. to ft.	Clay-brown 2 38
perforations from ft. to ft.	Rock : Sedimentary gray 38 203 30
perforations from ft. to ft.	Water pering at approx
(7) SCREENS: Well screen installed? Yes No	55 produced 10tg pm
Manufacturer's Name	flow increased to 7590m
Type Model No.	atapprox 77' and joodom
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	by 100' and 125g pm by 120'
Diam. Slot size Set from It. to It.	doubtoul if any ineverse
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Bottom of wellingray 203
s a pump test made? Yes No If yes, by whom?	Sedimentary rock
Yield: gal./min. with ft. drawdown after hrs.	Note -
" " " "	a pump test of several hours duration
" " "	is suggested to dotermine drawdown and
for test 125 gal./min. with Maxtt. drawdown after / hrs.	recovery characteristics before any
Artesian flow g.p.m.	Sizeable irrigation project is decided
Temperature of water Depth artesian flow encountered ft.	Work started 8-97 1979 Completed 8-38 1979
(9) CONSTRUCTION:	
Well seal-Material used Comenty 4 to 5 % bout nuite	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface toft. Diameter of well bore to bottom of sealfin.	Materials used and information reported above are true to my
Diameter of well bore to bottom of seal	best knowledge and belief
Number of sacks of cement used in well seal	[Signed] Date 8-28, 1979.
How was cement grout placed? Dumbed	Drilling Machine Operator's License No. 159
	Water Well Contractor's Certification:
The state of the s	This well was drilled under my jurisdiction and this report is
Was a drive shee used? \(\text{Vec that } \)	true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes ♠No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ♠ No	Name Dell PageWell Drilling
Type of water? depth of strata	Address 2586 Hwy 136 Veneta Organ
Method of sealing strata off	1000
Was well gravel packed? ☐ Yes % No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 104 Date 8-28 1979