NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

## STATE OF OREGON

(Please type or print) (Do not write above this line) State Well No. ...

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	
Name Ben Fisher	County Lane Driller's well number	
Address 88460 Fisher Road, Eugene, Or.	14 14 Section 26 T. 17S R. 5W	W.M.
(0) = 100 (1 1)	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	Tax Lot #200	
New Well Deepening Reconditioning Abandon	,	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 30'	ft.
Retary	Static level 27' ft. below land surface. Date 5/16/	780
Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date	
(5) CASING INSTALLED: Threaded   Welded		
(5) CASING INSTALLED: Threaded $\square$ Welded $\square$ 10	(12) WELL LOG: Diameter of well below casing	
"Diam. from ft. to ft. Gage	Depth drilled 140 ft. Depth of completed well 140	ft.
Diam. from	Formation: Describe color, texture, grain size and structure of mater	ials;
	and show thickness and nature of each stratum and aquifer penetre with at least one entry for each change of formation. Report each change	ated, ge in
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No.	position of Static Water Level and indicate principal water-bearing st	rata.
Type of perforator used	MATERIAL From To SW	VI.
Size of perforations in. by in.	Soil & clay 0 12	
perforations from ft. to ft.	Basalt	
perforations from ft. to ft.	Sandstone, blue & grey 105 140 27	7 •
perforations from ft. to ft.		
(7) SCREENS: Well screen installed?   Yes   XNo		
Manufacturer's Name		
Type Model No		
Diam Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.	77.77	
(8) WELL TESTS: Drawdown is amount water level is		
lowered below static level		
a pump test made? Yes X No If yes, by whom?	JUN - 3 198U	
Yield: gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT	
n n n	SALEM, OREGON	
" " " "		
gal./min. with 110st. drawdown after l hrs.		
A wan flow g.p.m.	-	
Temperature of water Depth artesian flow encountered ft.	Work started $5/16$ 1980 Completed $5/16$ 19	80
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5/16 19	
Well seal—Material used Cement grout	Drilling Machine Operator's Certification:	
Well sealed from land surface to 18 ft.	This well was constructed under my direct supervisi	on.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to best knowledge and belief.	my
Diameter of well bore below seal6 in.	[Signed] Machine Operator Date .5/20, 19.	
Number of sacks of cement used in well seal5	(Similar Operator)	
How was cement grout placed?Pressure grouted.	Drilling Machine Operator's License No. 386	
	Water Well Contractor's Certification:	-
The state of the s	This well was drilled under my jurisdiction and this repor	et ia
Transition of the state of the	true to the best of my knowledge and belief.	£ 15
Was a drive shoe used? ☐ Yes 答 No Plugs Size: location ft.  Did any strata contain unusable water? ☐ Yes ↑ No	Name Pitcher Pump & Drilling Company	
	(Person, firm or corporation) (Type or print)  Address 87829 Greenhill Road, Eugene, Or 9740	12
Type of water? depth of strata	Address 87829 Greenhill Road, Eugene, Or 9740	16
Method of sealing strata off	[Signed] af Puche	
Was well gravel packed? ☐ Yes K No Size of gravel:	(Water Well Contractor)	. 80
Gravel placed from ft. to ft.	Contractor's Encembe 140 Date	
(USE ADDITIONAL SH	EETS IF NECESSARY) 494	8-119