
File Original and First Copy with the STATE ENGINEER,



WATER WELL REPORT

LANE 13235 State Well No.

GINEER

STATE OF OREGON

SALEM, OREGON CIA	SALEM, OREGON CIAIL GALL GALL GALL GALL GALL GALL GALL		
(1) OWNER: SALEM, OREGOY!	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name Corps of Engineers	Was a pump test made? X Yes No If yes, by who		
Address 628 Pittock Block	Yield: 68 gal./min. with 50ft. drawdo		
Portland 5, Oregon	<u>" 70 " 50 "</u>	1 "	
(2) LOCATION OF WELL:	<u>" 70 " 50 "</u>	<u> </u>	
	Bailer test gal./min. with ft. drawdo	wn after hrs.	
GLI . WIL	Artesian flow g.p.m. Date		
	Temperature of water Was a chemical analysis r	nada? 🗆 Var 🗆 No	
Bearing and distance from section or subdivision corner	The second distribution of the second distributi		
1635 feet S. and 510 feet E. from NW corner	(12) WELL LOG: Diameter of well	inches.	
Sec. 28, T. 17 S., R. 5 W.W.M.	Depth drilled 75 ft. Depth of completed		
	Formation: Describe by color, character, size of mater show thickness of aquifers and the kind and nature of the stratum penaturated.	ial and structure, and	
	show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each	the material in each change of formation.	
	MATERIAL	FROM TO	
(3) TYPE OF WORK (check):			
	Soil	$\frac{1}{10}$ $\frac{1}{10}$ $\frac{1}{10}$	
New Well Deepening Reconditioning Abandon Labert Ab	Yellow clay	19	
vandonment, describe material and procedure in item 11.	Grey clay	19 28	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Fine silt & clay	28 49	
	_Cemented gravel	49 56	
Tamigation C Foot Well C Other C Cable A Jetted	Coarse sand (water)	56 75	
Irrigation ☐ Test Well ☐ Other			
(6) CASING INSTALLED: Threaded ☐ Welded X			
"Diam. from ft. to ft. Gage			
ft. Gage ft. Gage			
(7) DEDEODATIONS.			
(7) PERFORATIONS: Perforated? ☐ Yes ☑ No		-	
Type of perforator used		-	
SIZE of perforations in. by in.			
perforations from ft. to ft.		 	
perforations from ft. to ft.		 	
perforations from ft. to ft.		 	
perforations from			
perforations from ft. to ft.			
(8) SCREENS: Well screen installed Yes No			
(8) SCREENS: Well screen installed ☐ Yes ☐ Ño Manufacturer's Name			
Type Model No.		<u> </u>	
i Slot size Set from ft, to ft.			
Diam, Slot size Set from ft. to ft.	Work started 7/18/61 19 . Completed	7/28/61 19	
(a) CONSUDICATION.			
(9) CONSTRUCTION:	(13) PUMP:		
Was well gravel packed? ☐ Yes ♣No Size of gravel:	Manufacturer's Name	***************************************	
Gravel placed from ft. to ft.	Type: H.P.		
Was a surface seal provided? Tyes I No To what depth? ft.			
Material used in seal— Cement	Well Driller's Statement:		
Did any strata contain unusable water? Yes No	This well was drilled under my jurisdiction	and this report is	
Type of water? Depth of strata	true to the best of my knowledge and belief.	*	
Method of sealing strata off	MARKE W Drid I I trace 2. Drawn	Commisso	
/10) WATER IEVELS.		SCIVICEype or print)	
(10) WATER LEVELS:	Address 285 So. 32nd St.	- ,	
Static level 10 ft. below land surface Date 7/28/61	Springfield, Oregon		
Artesian pressure lbs. per square inch Date	Driller's well number	7461	
	,		
Log Accepted by:	1,1,4-11,0		
Log Accepted by:	[Signed] Walt Wilson		
[Sign Date 13 September 1961	(Well Driller)	163	
Mento	[Signed] Walt Wulson (Well Driller) License No. 268 Date 8/5	/61 , 19	