

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

RECEIVED
MAR 21 1972

WATER WELL REPORT
STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 (Please type or print)
within 30 days from the date of well completion. SALEM, OREGON (Do not write above this line)

State Well No. 17/5W-29
State Permit No. LANE
13332

(1) OWNER:

Name Veneta Seventh Day Adventist Church
Address Veneta, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Cable Dug
Driven Jetted Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

6 3/8" AD Threading Welded
Diam. from 0 ft. to 74 1/2 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Bailer test 30 gal./min. with 30 ft. drawdown after 1 hrs.
Artesian flow g.p.m.

(9) CONSTRUCTION:

Well seal—Material used Bentonite + drillings
Well sealed from land surface to 24 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 14 sacks
Brand name of bentonite yellowstone
Number of pounds of bentonite per 100 gallons of water 175 lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lane Driller's well number
1/4 1/4 Section 29 T. 17S R. 5W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 47 ft.
Static level 32 ft. below land surface. Date 2-29-72
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Cased well depth 6
Depth drilled 75 ft. Depth of completed well 74 1/2 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil	0	2 1/2	
Clay - brown	2	30	
Clay - bluegray	30	47	
Clay + sand	47	52	
Sand & gravel - Compact	52	67	
Sand & gravel - water bearing	67	75	32
bottom of well in dark water bearing sand & gravel	74 1/2		

Work started 2-23 1972 Completed 2-29 1972
Date well drilling machine moved off of well 2-29 1972

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Dele Page Date 2-29, 1972
(Drilling Machine Operator)

Drilling Machine Operator's License No. 159

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Hayes + Page Well Drilling Oreg Ltd.
(Person, firm or corporation) (Type or print)

Address Rt 3 Box 218, Veneta, Oregon

[Signed] Dele Page
(Water Well Contractor)

Contractor's License No. 104 Date 2-29, 1972