NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report

are to be filed with the

water well report

water resources department, CTO 2 1980

state of oregon

within 30 days from the water RESOURCES DEParts type or print)

of well completion.

SALEM. OREGON

State Well No. 17/500-3/6
State Permit No. LANE

13439

(1) OWNER:	(10) LOCATION OF WELL: County LANE Driller's well number 2881/22
Name FREDRICKS SUNNY STATION (RW)	
Address 25547 Hwy 126	14 NW 14 Section 31 T. 17 R. 5W W.M.
VENETA, OREGON	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 80 ft.
Pery □ Driven □ □ □ Domestic ☑ Industrial □ Municipal □	Static level 42 ft. below land surface. Date 9/19/80
Dug	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded X 6	(12) WELL LOG: Diameter of well below casing Depth drilled 82 ft. Depth of completed well 82 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
(6) PERFORATIONS: Perforated? □ Yes 営 No. Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	GRAVEL 0 4
perforations from ft. toft.	YELLOW CLAY & GRAVEL MIXED 4 53
perforations from ft. to ft.	GREEN CLAY & GRAVEL 53 62
perforations from	GRAVEL & GREEN CLAY 72 74
(E) CODERIO	BROWN CLAY & GRAVEL 74 80° 42
(7) SCREENS: Well screen installed? Yes Y No	GRAVEL 80 82 42
Manufacturer's Name Model No	
Diam. Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
a pump test made? Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
<i>n</i> . <i>n n n</i>	
17 10 1	
er test 17 gal./min. with 40 ft. drawdown after 1 hrs.	
Artesian flow g.p.m.	
Temperature of water 51 Depth artesian flow encountered ft.	Work started 9/15/ 1980 Completed 9/19/ 1980
(9) CONSTRUCTION:	Date well drilling machine moved off of well 9/19/ 1980
Well seal-Material used PORTLAND CEMENT TYPE III	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] A Date9/19/., 19.80
Number of sacks of cement used in well sealsacks How was cement group placed? METHOD 'I'C'I USED	Drilling Machine Operator's License No
How was cement grout placed? METHOD "C" USED	Diffing Machine Operators Dicesso 110
The state of the s	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? X□ Yes □ No Plugs Size: location ft.	true to the best of my knowledge and belief. Nome CARTER'S DRILLING & PUMP SERVICE
Did any strata contain unusable water? Yes X No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address P.O. Box 46 SPRINGFIELD OREGON 97477
Method of sealing strata off	simulation of the
Was well gravel packed? Tes Yes Yoo Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed fromft. to ft.	Contractor's License No. 126 Date 9/19/ , 1980