NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

TER WELL REPORT WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 TE OF OREGON (Please type or print)

within 30 days from the date

of well completion. APK 5 1968 not write a	bove this line)	12700	
WATER RESOURCES DEPT.		<u> 13526</u>	
(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:		
Name BILL MCCABE	County LANE Driller's well number		
Address 85766 PINE GROVE RD	NE 4 NE 4 Section 32 T. 175 R. 5W W.M.		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivis		
4	25'NEB'E OF THE	SW PROPERTY	
New Well Deepening Reconditioning Abandon Lift abandonment, describe material and procedure in Item 12.	CORNER,		
	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found		
Rotary 🗗 Driven 🛘 Domestic 🗹 Industrial 🖂 Municipal 🖂	Static level 12 ft. below land	surface. Date 3 APRIL?	
Dug	· • • • • • • • • • • • • • • • • • •	re inch. Date	
(5) CASING INSTALLED: Threaded Welded Welded 5. 4. 5. 6. 128 ft. 6 28 ft. 6 27.5	(12) WELL LOG: Diameter of well	pelow casing	
"Diam. from ft. to ft. Gage	Depth drilled 20 ft. Depth of compl		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	and structure of materials;	
(6) PERFORATIONS: Perforated? Yes Pro.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Report each change in	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	FILL MITL CLAYEY GRAVEL	0 15 -	
perforations from ft. to ft.	CLAY RED BRN - GREY	15 30 -	
perforations from ft. to ft.	SANDY CLAY	30 38 15	
perforations fromft. toft.	CLAYEY GRAVELLY SAND	38 45 "	
(7) SCREENS: Well screen installed? Yes No	SANDY GRAVEL	45 57 "	
Manufacturer's Name	GREY CLAY CLAYEY SANDY GRAVEL	57 68 -	
Type Model No	SANDY GRAVEL	68 25 12 75 80 12	
Diam Slot size Set from ft. to ft.	JAND! GRAVEE	15 80 12	
Diam Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
lowered below static level AiR Was a pump test made? A Yes No If yes, by whom? DRILLER			
d: 30 gal./min. with 63 ft. drawdown after 1 hrs.			
<i>"</i>			
" " " " " " " " " " " " " " " " " " "			
Bailer test gal./min. with ft. drawdown after hrs.			
tesian flow g.p.m.			
temperature of water 52 Depth artesian flow encountered ft.	Work started 31 MARCH 1979 Complete	d 4 APRIL 1979	
(9) CONSTRUCTION:	Date well drilling machine moved off of well		
Vell seal—Material used CEMENIT + 5% BENTON (TE	Drilling Machine Operator's Certification:	CITAL T	
Well sealed from land surface to 2.5 ft. Diameter of well bore to bottom of seal 10 in.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore below seal in.	best knowledge and belief. [Signed] Walter N. White	ALADON DO	
Tumber of sacks of cement used in well seal	(Drilling Machine Operator)		
Now was cement grout placed? PVMPED TO BOITOM	Drilling Machine Operator's License No. 1086		
OF 10" HOE	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is		
Vas a drive shoe used? 🔁 Yes 🗌 No Plugs Size: location ft.	true to the best of my knowledge and belief.		
old any strata contain unusable water? 🏲 Yes 🗌 No	Name W. N. W. H. I.T. E. (Person, firm or corporation) (Type or print)		
ype of water? SURFACE depth of strata 1'70241	Address 91769 PRAIRIE RD, Ju		
Tethod of sealing strata off CASED & GROVTED	[Signed] Walter M White	97448	
Vas well gravel packed? ☐ Yes ☑ No Size of gravel:	(Water Well Contra		
ravel placed from ft. to ft.	Contractor's License No. 638. Date 4	MARCH , 1979	