NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## RECEIVED

WATER WELL REPORT 03 0 1974

STATE OF OREGON State Well No. 175 6W - 29

(Please type or print) STATE ENGINEER

(Do not write above this in LEM, OREGON State Permit No. LANE 14.343

(1) OWNER:	(10) LOCATION OF WELL:
Name Robert JJ WRIGht	County LANE Driller's well number
Address 88838 HALE Rd	14 14 Section 2 9 T. /75 R. 6 W W.M.
Noti Opegow 97461	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well   Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(8) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 78 ft.
Rotary Driven Domestic D Industrial Municipal	Static level 26 ft. below land surface. Date 12/3/74
Cable	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded Welded Welded W. Diam, from 7 / /2 ft. to 3.8 /2 ft. Gage 1250	(12) WELL LOG: Diameter of well below casing
" Diam. fromft. to	
ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated?   Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	TopsoiL 02
perforations fromft. toft.	BROWN C/AY 2 27
perforations from ft. to ft.	Blue C/AY 27 32
perforations from ft. to ft.	Type 55' 32 100
(7) SCREENS: Well screen installed?   Yes   Yes	
Manufacturer's Name	
TypeModel No.	5,
Diam. Slot size Set from ft. to ft.	12 HP YALIG BEARELEY
Diam. Slot size Set from ft. to ft.	PUMP INSTALLED ON
(8) WELL TESTS. Drawdown is amount water level is	12-20-74 PUMP WAS
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	OPERATED AT 5 GPM
Was a pump test made? Yes \( \subseteq No \) If yes, by whom? \( \subseteq R/L/LFP \)	4 100 # PRESSURE FOR
Yield: 5 gal./min. with 30 ft. drawdown after 4 hrs.	4 400/13
n H . n	The second of th
1	
Baller test 7 gal./min. with maxft. drawdown after 2 hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started /2/10 1974 Completed /2/13 1974
(9) CONSTRUCTION:	Date well drilling machine moved off of well /2/13 1974
Well seal-Material used Cement GROUT - DEN towite	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below seal	[Signed] Taul Christians Date 12/6, 1974
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No. 6/2
Number of sacks of bentonite used in well seal sacks	
Brand name of bentonite /2/10wSlove	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.	# This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes Plugs Size: location ft.	Name MARK CHRISTEUSEN
Did any strata contain unusable water? Tyes W No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 1772 8 0 438 C EUGENE 9740/
Method of sealing strata off	[Signed] Mark Janustonsen
Was well gravel packed?  Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 97 Date 12/17 19.74