The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well complete.

JUN 1 6 1975 state Well No. 125/6w - 29 dc

STATE ENGINEES ate Permit No.

(Do not write above this line SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Swanson Bros Lumber Co	County Lane Driller's well number
Address Noti Oregon	SE 454 4 Section 29 T. 175 R. 642 W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	The state of the s
New Well  Deepening □ Reconditioning □ Abandon □	at west end of planer bldg
If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found Trace a 114 ft.
Rotary	Static level 41 ft. below land surface. Date 5-29-25
Dug	Artesian pressure lbs. per square inch. Date
CACING INCOMITED.	
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
678 &D' Diam. from ft. to 207 ft. Gage 250	Depth drilled 157 ft. Depth of completed well 157 ft.
	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
(6) PERFORATIONS: Perforated? IT Yes A No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Clay 0 143
perforations from ft. to ft.	Rock- Sedimentery-grow 142 157 49
perforations from ft. to ft.	water bearing at report
perforations from ft. to ft.	95 with good increase
(7) SCREENS: Well screen installed? I ves & No.	noted between 105 4110
	Exact depth of lower
Manufacturer's Name	increases not determined
Type Model No.	(Final bailing showed
Diam. Slot size Set from ft. to ft.	indications of good water
Diam. Slot size Set from ft. to ft.	bearing zone in last few
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	st of hole)
Was a pump test made?  Yes No If yes, by whom?	Bettem of well in gray 157
Yield: gal./min. with ft. drawdown after hrs.	Sedimentary rock
" " "	
n n n	
Bailer test / gal./min. with / ft. drawdown after / hrs.	10 10 10 10 10 10 10 10 10 10 10 10 10 1
rtesian flow g.p.m.	
nperature of water Depth artesian flow encountered ft.	Work started 5-27 19 7-5 Completed 5-29 1975
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5-29 1975
Well seal-Material used Coment	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Date 5-29, 19.25
Number of sacks of cement used in well sealsacks	(Drilling Machige Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No./5.7
Brand name of bentonite	777 J 777 77 Ct ( )
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used?   Yes No Plugs Size: location ft.	
Did any strata contain unusable water?   Yes No	Name Hayes 4 Lage Well Drilling Orage to
Type of water? depth of strata	Address 2586/ Huy 126 Veneta Oregon
Method of sealing strata off	donale.
	[Signed]
	landa and the control of the control
Gravel placed fromft. toft.	Contractor's License No. 104 Date 5-29, 19.75