## STATE OF OREGON WATER WELL REPORT

(as required by ORS 537.765)

## RECEIVED JUL 2 7 1984

HTEVEELLABE COBINITA INK BL

185/4W-19

(for official use only)

(1) OWNER:	(10) LOCATION OF WELL by lega	l description:
Name C. A. Bowers	County Lane 4 4	of Section 19 of
Address 31479 Camas Lane	Township 185 Banga	wм.
City Eugene State Or	(Township is North or South)	(Range is East or West)
(2) TYPE OF WORK (check):	Tax Lot Lot Block Subdivision  MAILING ADDRESS OF WELL (or nearest address) SAli	
	MAINTO ADDITION OF WIND (OF Bearest actives)	
New Well 以 Deepening □ Reconditioning □ Abandon □ If abandonment, describe material and procedure in Item 12.		
	(11) WATER LEVEL of COMPLET	ren wett.
(3) TYPE OF WELL: (4) PROPOSED USE (check):		
Rotary Air 🕅 Driven 🗆 Domestic 🖾 Industrial 🗆 Municipal 🗆 Thermal:	Depth at which water was first found	210 ft.
Rotary Mud Dug Irrigation Withdrawal Reinjection		land surface. Date 7-25-84
Other: Piezometric Grounding Test		square inch. Date
(5) CASING INSTALLED: Steel Plastic Welded	Depth drilled 295 ft. Depth of completed well 295 ft.  Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of	
"Diam. fromft. toft. Gauge	formation. Report each change in position of Static Wat water-bearing strata.	er Level and indicate principal
LINER INSTALLED: Steel   Plastic	MATERIAL	From To SWL
Threaded Welded	Topsoil	0 1
"Diam. fromft. toft. Gauge	Brown Clay	1 4
(6) PERFORATIONS: Perforated? ☐ Yes ⋈ No	Red Brown Gray Green Cono.	4 241
Size of perforations in. by in.	Brown Gray Cong.	24 35
ft. to ft.	Gray Green Cono.	35 46
ft. toft.	Brown Claystone	46 50
perforations from ft. to ft.	Gray Green Cong.	50 63
(7) SCREENS: Well screen installed?   Yes  No	Brown Gray Cong.	63 67
Manufacturer's Name	Gray Green Cong.	67 110
TypeModel No	Brown Cong.	118 114
Diam Slot Size Set from ft. to ft.	Gray Green Cong.	114 215
Diam. Slot Size Strom ft. to ft.	Brown Cong.	215 221
Drawdown is amount water level is lowered	Gray Green Basalt	221 265
(8) WELL TESTS:  below static level	Gray Green Cong.	265 295
Was a pump test made?  Yes  No If yes, by whom?		
i: gal./min. with ft. drawdown after hrs.		
7 , , , , , , , , , , , , , , , , , , ,		
Air test 2 gal./min. with drill stem at 295 ft. 1 hrs.		-
Bailer test gal./min. with ft. drawdown after hrs.		=
Artesian flow g.p.m.		
perature of water Depth artesian flow encountered ft.	Date work started 7-25-84 /complete	d 7-25-84
(9) CONSTRUCTION: Special standards: Yes □ No 🛚		
Well seal—Material used Portland Cement	Date well drilling machine moved off of well	7–25 19 84
Well sealed from land surface toft.	(unbonded) Water Well Constructor Certification (if applicable):	
Diameter of well bore to bottom of seal	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.  [Signed]	
Diameter of well bore below seal		
Amount of sealing material	[Dighet]	
	(bonded) Water Well Constructor Certification:	
	Bond 05U452863 Issued by: United Pacific Ins. (Surety Company Name)	
Was pump installed?	On behalf of Casev Jones Well Drilling Co Inc.	
Was a drive shoe used? 🔲 Yes 🛱 No Plugs Size: location ft.	(type or print name of Water Well Constructor)	
Did any strata contain unusable water?   Yes   No not testd	This well was drilled under my jurisdiction and this report is true to the	
Type of Water? depth of strata	best of my knowledge and belief:	
Method of sealing strata off	(Signed) 7-25-84	
Was well gravel packed? Yes X No Size of gravel:	(Wester Well Constructor)	
Gravel placed fromft. toft. (Dated)		
	7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7	