

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

STATE OF OREGON

MAY 25 1973 State Well No.

(Please type or print)

STATE ENGINEER

(Do not write above this line)

SALEM OREGON

17S/1E-1aa
LANE 14914

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

(1) OWNER:

Name KENNETH HEATH
Address VIDA OREGON

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Cable
Driven Jetted
Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded

6" Diam. from 0 ft. to 20 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Blow test 6.0 gal./min. with 220 ft. drawdown after 1 hrs.
Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 25 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL: VIDA, Lane TR

County LANE Driller's well number
NE 1/4 NE 1/4 Section 1 T.17S R. 1E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 230 ft.
Static level 20 ft. below land surface. Date 5/2/73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 240 ft. Depth of completed well 240 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	3	
CLAY + BOULDERS	3	15	
Red Shell	15	50	
BLUE ROCK	30	85	
BLACK BASALTS	85	140	
Red Shell	140	150	
BLUE ROCK HARD	150	170	
GRAY ROCK HARD	170	185	
BLACK BASALTS	185	205	
Blue ROCK	205	215	
BLACK BASALTS	215	225	
Red Shell	225	240	20

Work started 5/1 1973 Completed 5/2 1973
Date well drilling machine moved off of well 5/2 1973

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief

[Signed] Est. Pulliam Date 5/3, 1973
(Drilling Machine Operator)

Drilling Machine Operator's License No. 813

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name W.W. DRINKING
(Person, firm or corporation) (Type or print)

Address 2320 MAIN SPRINGFIELD, ORE

[Signed] Frank Wilson
(Water Well Contractor)

Contractor's License No. 562 Date 5/3, 1973