## STATE OF OREGON

WATER WELL REPORT PAR WWC PECFIVE

18</11/1-330

1 L	REUEIVE	L	State Well No.	185/1	W(
Port.	Cener DEC 19 1983  PLEASE TYPRIMATERY RESOURCES			ANE	15146
· w	PLEASE TYPWATER RESOURCES		State Permit No	₩ 1.3.1.7.1 <del></del>	4
	Salem. Oregoi	-			
	Manifest Common	-			

(1) OWNER:	(10) LOCATION OF WELL:	
Name Fall Creek Christian Church	County Lane Driller's well number 3713/670	
AddressP.O. Box "C"		W.M
City Fall Creek State Oregon	Tax Lot # 502 Lot Blk Subdivision	
(2) TYPE OF WORK (check):	Address at well location:	
New Well Deepening Reconditioning Abandon C	(11) WATER LEVEL: Completed well.	
if abandonment, describe material and procedure in Item 12.	Depth at which water was first found 60	ft.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 18 ft. below land surface. Date 12/8	<b>/83</b>
Rotary Air 🛣 Driven 🗆 Domestic 🔀 Industrial 🗆 Municipal 🗆	Artesian pressure lbs. per square inch. Date	
Rotary Mud   Dug   Irrigation   Test Well   Other	(12) WELL LOG: Diameter of well below casing 6**	
	Depth drilled 87 ft. Depth of completed well 87	ft.
(5) CASING INSTALLED: Steel  Plastic Threaded  Welded X	Formation: Describe color, texture, grain size and structure of materials; and	show
6" Diam. from	thickness and nature of each stratum and aquifer penetrated, with at least one for each change of formation. Report each change in position of Static Water	entry .
"Diam from ft. to ft. Gauge	and indicate principal water-bearing strata.	TYE ACT
LINER INSTALLED:	MATERIAL From To SW	л.
	Top Soil 0 5	
	Brown Shale 5 8	
(6) PERFORATIONS: Perforated? ☐ Yes ¾ No	Black Basalt 8 60	
Type of perforator used		8
Size of perforations in. by in.		8
perforations from ft. to ft.	DIGON DANGED	
perforations from ft. to ft.	= 12	
perforations from ft. to ft,		
(7) SCREENS: Well screen installed?   Yes You No		
Manufacturer's Name		
Type Model No		
Diam. Slot Size Set from ft. to ft.	h.	
Diam. Slot Size Set from ft. to ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Delow static level	, AMA	
Was a pump test made? ☐ Yes. X☐ No If yes, by whom?		
d: gal./min. with ft. drawdown after hrs.		
Air test 40 gal/min. with drill stem at 80 ft. 1 hrs.		
Bailer test gal./min. with ft. drawdown after hrs.	The state of the s	
Artesian flow g.p.m.  hperature of water 52 Depth artesian flow encountered ft.	Work started 12/5/ 19 83 Completed 12/8/83	
	WOLK STATE CO.	19 19 <b>83</b>
(9) CONSTRUCTION: Special standards: Yes $\square$ No $\square$	Date rest at ming mount in rest and a second	
Well seal—Material used	(unbonded) Water Well Constructor Certification (if applicab	
Well sealed from land surface to	This well was constructed under my direct supervision. Materials and information reported above are true to my best knowledge and be	s used elief.
Diameter of well bore to bottom of seal	[Signed]	83
Diameter of well bore below sealin.	- War To the table of	
Number of sacks of cement used in well seal	Bonded Water Well Constructor Certification:  Bond U3-66353  Issued by: United Pacific	
How was cement grout placed? Re trot	Bond U3-05353 Issued by: Officed 1 actific Surety Company Name	
	This well was drilled under my jurisdiction and this report is to	rue to
Was pump installed?Type HP Depth ft.	the best of my knowledge and belief.  Name Carter's Drilling & Pump Service	
Was a drive shoe used? ☐ Yes X No Plugs	(Person, firm or corporation)	nt)
Did any strata contain unusable water?   Yes A No	Address 330 S. 3rd - P.O. Box 46 Som northeld	, Ore
Type of Water? depth of strata	[Signed] James J. (with)	
Method of sealing strata off	Water Well Constructor 19/8/	83
Was well gravel packed?	Date, 19	
Gravel placed fromft. toft.		<del></del> -
	WATER RECALDED DENATED SPACE	വെ മവ