NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORTECTIVED

- STATE OF OREGON

(Please type or print) MAY 1 1975 State Well No. 180 200-14 C(Do not write above this lineSTATE ENGINEER State Permit MAY 1 5444

(1) OWNER:	(10) LOCATION OF WELL:			
Name Jasper Store (Calvin Snyder)	·		1107-	CD
Address Jasper, Oregon				
· · · · · · · · · · · · · · · · · · ·	% S Wesetion 11 T. 18	A		W.M
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corne	<u>r. </u>	
New Well Deepening Reconditioning Abandon	A CONTRACTOR AND A CONT	·	<u> </u>	<u> 35 M.</u>
If abandonment, describe material and procedure in Item 12.	(11) THAMED THEFT			·
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.			
Rotary Driven D	Depth at which water was first found 203 ff			
Cable Jetted Domestic Industrial Municipal Dug Bored Irrigation Test Well Other		urfaçe.	Date 3_	-13-75
	Artesian pressure lbs. per squar	e inch.	Date	
CASING INSTALLED: Threaded [] Welded [X	(12) WELL LOG: Diameter of well by			
6 "Diam. from 0 ft. to 50 ft. Gage 250	Diameter of well below casing			
" Diam. fromft. to	bepth drilled 300 ft. Depth of completed well 300 ft			
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each stratur	nd struct	ture of n	naterials
PERFORATIONS: Perforated 2 Voc. 55 No.	with at least one entry for each change of format	ion Rend	art pach c	ohanaa is
Teriorated: Tes X No.	position of Static Water Level and indicate prin	cipal wat	er-bearin	ıg strata
		From	То	swl
		0	2	
perforations from ft. to ft.	Large Gravel	2	15	
perforations fromft. toft.	Blue Shale	15	251	
perforations from ft. to ft.	Brown Shale	251	270	
(7) SCREENS: Well screen installed? Yes X No	- Blue Shale	270	_300	
Manufacturer's Name		+		
Type Model No.	- <u>.</u>			
Diam. Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.	LAN.			
(8) WELL TESTS: Drawdown is amount water level is				
lowered below static level				
Was a pump test made? X Yes \(\text{No If yes, by whom?} \) Driller Yield: \(\text{Y-x} \) \(\text{gal/min. with } \) 162 ft drawdown effort \(In a second of the control of th				
103 tc. drawdown after // hrs.				
Marie and the second se		- $+$		
The state of the s	7 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
Bailer test No gal./min, with ft, drawdown after hrs.				
Artesian flow g.p.m.	10 mm 2 mm			
perature of water 51 Depth artesian flow encounteredft.	Work started 3-10 19.75 Completed	3-1	13	1975
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3 - 3		1975
Well seal—Material used Portland Cement	i.			1917
Well sealed from land surface to 10	Drilling Machine Operator's Certification: This well was constructed under my	dinaat		
Diameter of well bore to bottom of seal 9 7/8 in.	Materials used and information reported a	bove a	superv ce true	to my
Diameter of well bore below seal	best knowledge and belief.			
Number of sacks of cement used in well seal 12 sacks	[Signed] (Drilling Machine Operator)	ate ユニ	25,	19/2
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No	717	7	
Brand name of bentonite		. 4		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of waterlbs./100 gals.	This well was drilled under my jurisdic true to the best of my knowledge and belie	tion and	this re	port is
Was a drive shoe used? ▼ Yes □ No Plugs Size: location ft.	Name Carter's Drilling & Pump Service			
Did any strata contain unusable water? Yes KNo	(Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address P. O. Box 46 Springfield, Oregon 97477			
Method of sealing strata off	[Signal]		Z	
Was well gravel packed? ☐ Yes No Size of gravel:	[Signed] (Water Well Contrac	tor)		
Gravel placed from ft. to ft.	- 7	-25		10 75