NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97810 G2 7 1975

Within 30 days from the date of well completion WATER RESOURCES (PEPGwrite above this line)

State Well No. ....

SALEM, OREGON	1 7
(1) OWNER:	(10) LOCATION OF WELL:
Name STafford Shire	County Lange Driller's well number
Address Bay 177 - G	14 14 Section 19 T. 18 S R. 2 W W.M.
Eugene, ore	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well   Deepening   Reconditioning   Abandon    Abandon   ■	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Part of the state
Rotary Diven Domestic Industrial Municipal	Static level / O ft. below land surface. Date
Cable	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded Welded D. "Diam. from 2 ft. to 7.5 ft. Gage 250"  "Diam. from ft. to ft. Gage "Diam. from ft. to ft. Gage ft. G	(12) WELL LOG: Diameter of well below casing  Depth drilled / 7.5 ft. Depth of completed well / 7.5 ft.  Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Pres   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used / Or C	MATERIAL - From To SWL
Size of perforations in. by in.	Brown Clay & grave 0 20
780 perforations from 80 ft. to 58 ft.	Count (rand 20 25
perforations from ft. to ft.	Com of the 20
perforations from ft. to ft.	CIV 9 0 - and 15 80
(7) SCREENS: Well screen installed?   Wes End	9 ravy / 5 and 80 85
Manufacturer's Name	
Type Model No.	Clay & grave 85 87
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	50ml 9-gm
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	5Treak 1 51 58
Was a pump test made? ☐ Yes ☐ No If yes, by whom? (\(\mu\) \(\mu\))	g Clay gravel 88/60
Yield: 223 gal./min. with 7.3 ft. drawdown after 24 hrs.	
" " "	Sand & grant 160 170
" " "	D/1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Bailer test gal./min. with ft. drawdown after hrs.	13/4 C/24 176 175
Artesian flow g.p.m.	
erature of water Depth artesian flow encounteredft.	Work started 7/14 1975 Completed 7/3/ 1975
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8/// 1975
Well seal-Material used Ceamen	Drilling Machine Operator's Certification:
Well sealed from land surface to 70 tt.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal	best knowledge and belief.
Diameter of well bore below seal	[Signed] Date 8/ 8 19?
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location ft.	true to the best of my knowledge and belief.  Name W.W. Drilling & Pump Service
Did any strata contain unusable water?	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 2320 Main St. Spfd. Oregon 97477
Method of sealing strata off	1. 11.1
Was well gravel packed? ☐ Yes ☐ No Size of gravel: 1 3/4	[Signed](Water Well Contractor)
Gravel placed from 70 ft. to 175 ft.	Contractor's License No. 562 Date 8/1/ 19.75