NOTICE TO WATER WELL CONTRACTOR E VE VE The original and first copy of this report are to be 100 Martin ENCLYPTION OF THE PROCESS OF THE PROC

STATE ENGINEER, SALEM, OREGON 97310 ENGINEISTATE OF OREGON within 30 days from the date of the CREGON of well completion.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount we lowered below static levers.	ater level is	-
Name Pacific Power & Light Co. (M.O.E 2)	Was a pump test made? ★ Yes ☐ No If yes, by whom?	0	r's
Address 550 Main Street	Yield: 1700 gal./min. with 9 6 ft. drawdow		hrs.
Springfield, Oregon 97477	" " "		,,
(2) LOCATION OF WELL:))		**
Tone	Bailer test gal./min. with ft. drawdov	wn after	hrs.
County Lane Driller's well number	Artesian flow g.p.m. Date		
74 74 Section — 1. 1t.	W.M. Temperature of water 520 Was a chemical analysis m	ıade? □ Yes	□ No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below ca	sing 16"	-
	سرب ا	22	
	200		ft.
	Formation: Describe by color, character, size of material show thickness of aquifiers and the kind and nature of t stratum penetrated, with at least one entry for each ch	he material in ange of form	e, and n each nation.
	MATERIAL *	FROM '	TO
(3) TYPE OF WORK (check):	Top Soil	0	6
New Well 🕇 Deepening 🗌 Reconditioning 🗌 Aband	on Gravel, Sand & Small Cobbles	6	10
andonment, describe material and procedure in Item 12.	Coarse Gravel - Heavy Clay	10	21
(4) PROPOSED USE (check): (5) TYPE OF WE	LL: Sand, Gravel & Slight Clay	21	24
Rotary O Driven	Clean Sand & Gravel	24	30
Cable Jetted	Sand-Gravel-Clay	30	55
Irrigation Test Well Other Dug Bored			
(6) CASING INSTALLED: Threaded □ Welded ₽			
16	811		
"Diam. fromft. toft. Gage	· ·		
"Diam. from ft. to ft. Gage	1		
(7) PERFORATIONS: Perforated? XYes \(\square\) No			
Type of perforator used Torch			
Size of perforations 4 in. by 2 in.			
Torch 22 ft. to 47	ft.		•
ft. to	ft.		
perforations from ft. to	ft		
perforations from ft. to	ft.		
perforations from ft. to	ft.		
(8) SCREENS: Well screen installed? ☐ Yes 🗳 No			•
Manufacturer's Name	· · · · · · · · · · · · · · · · · · ·		
Model No.	1		
h, Slot size Set from ft. to	Work started 4/12 19 05 Completed 4	/23/	1965
Diam. Slot size Set from ft. to		23/	1965
(9) CONSTRUCTION:	(13) PUMP:		
Bentonite		: 1	
well seal-material used in seal	Manufacturer's Name		
Depth of seal ft. Was a packer used? Diameter of well bore to bottom of seal in.	Type: H	.P	······································
	Water Well Contractor's Certification:	**************************************	
Were any loose strata cemented off? Yes No Depth			1 +
Was a drive shoe used? A Yes ☐ No	This well was drilled under my jurisdiction a	nd this rep	ort is
Was well gravel packed? Yes No Size of gravel:	true to the best of my knowledge and belief.	• •	
Gravel placed from ft. to ft.	NAME Carter's Drilling & Pump Serv		·
Did any strata contain unusuable water? 🗌 Yes 🔼 No	205 Courth and St. Commings	e or print)	•^~
Type of water? depth of strata	Address 525 South 2nd St. Springire	الم مريد	,011
Method of sealing strata off	Drilling Machine Operator's License No.	748	
(10) WATER LEVELS:			
Static level 7'6" ft. below land surface Date 4/23/6	[Signed] (Water Well Contractor)		
Artesian pressure lbs. per square inch Date	Contractor's License No. 126 Date 5/4/	1	₉ 65