NOTICE TO WATER WELL CONTRACTOR

The original and first copy.

Of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON \$7310E CINCINETATE OF OREGON within 30 days from the date of well completion.

State Well No. 18/3 w -1
State Permit NoLANE 16/0/

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water lowered below static level	r level is
Name Pacific Power & Light Co (M.O.E.) 3	Was a pump test made? [▼Yes ☐ No If yes, by whom?	
Address 550 Main Street	Yield: 1000 gal./min. with 9 611 ft. drawdown a	fter 30 hrs.
Springfield, Oregon 97477	23 23	**
(2) LOCATION OF WELL:	"	,,
T	Bailer test gal./min. with ft. drawdown	after hrs.
7 7.1 70	Artesian flow g.p.m. Date	
/4 /4 5000001 20 20 20 20 20 20 20 20 20 20 20 20 20	Temperature of water 52° Was a chemical analysis made	a? 🗌 Yes 📋 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing	g 16
	Depth drilled 56 ft. Depth of completed well	56 _{ft.}
	Formation: Describe by color, character, size of material an show thickness of aquifiers and the kind and nature of the stratum penetrated, with at least one entry for each chang	material in each
	1	
(9) WYDE OF WORK (sheets).		ROM TO
(3) TYPE OF WORK (check):		0 4
Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		4 14
bandonment, describe material and procedure in Item 12.	Coarse Gravel - Large Cobbles	
(4) PROPOSED USE (check): (5) TYPE OF WELL:		14 24
Domestic Industrial Municipal Rotary Driven	Gravel, Small Cobbles - Clay	
Cable Jetted		24 28
Irrigation Test Well Other Dug Bored		28 44
(6) CASING INSTALLED: Threaded Welded	Sand - Gravel - Clay Mixed	LILI 56
16 "Diam, from 0 ft. to 56 ft. Gage 3/8"		
ft. toft. Gage		
ft. Gage		
(7) PERFORATIONS: Perforated? Z Yes 🗆 No		
Type of perforator used Torch		
Size of perforations 14 in. by 15 in.		
Torch perforations from 22 ft. to 47 ft.	· · · · · · · · · · · · · · · · · · ·	
perforations from ft. to ft.		
perforations from		
perforations fromft. toft.		
perforations from ft. to ft.		
(8) SCREENS: Well screen installed? ☐ Yes ¾ No		
Manufacturer's Name		
Model No.		
Selm, Slot size Set from ft. to ft.	Work started 5/17/ 1965 . Completed 6/11/	1965
Diam, Slot size Set from ft. to ft.	Work started 5/17/ 1965. Completed 6/11/ Date well drilling machine moved off of well 6/11/	1965
(9) CONSTRUCTION:		
	(13) PUMP:	
Well seal—Material used in seal Bentonite	Manufacturer's Name	
Depth of sealft. Was a packer used?	Type: H.P	
Diameter of well bore to bottom of seal in.	Water Well Contractor's Certification:	
Were any loose strata cemented off? Yes Depth	water wen contractor's certification.	
Was a drive shoe used? 🖰 Yes 🔲 No	This well was drilled under my jurisdiction and this report is	
Was well gravel packed? Yes No Size of gravel:	true to the best of my knowledge and belief.	
Gravel placed from ft. to ft.	NAME Carter's Drilling & Pump Service	
Did any strata contain unusuable water? Yes No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 325 South 2nd St. Springfield, Oregon	
Method of sealing strata off	= Drilling Machine Operator's License No. 118	
(10) WATER LEVELS:	Danning Machine Spectrus & Lincellise 110.	
Static level 11'6" ft. below land surface Date 6/4/65	[Signed] (Water Well Contractor)	
Static level LL'O" ft. below land surface Date 14/02 Artesian pressure lbs. per square inch Date		₁₀ 65
ins. her sange incu hase	Contractor's License No. 126 Date 6/22/	19