

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97101 within 30 days from the date of well completion

WATER WELL REPORT

STATE OF OREGON (Please type or print)

(Do not write above this line)

G-4708

RECEIVED OCT 31 1968 STATE ENGINEER SALEM, OREGON

RECEIVED NOV 12 1968 STATE ENGINEER SALEM, OREGON

State No. 18/3w-12-1d State Permit No. LANE 16204

(1) OWNER:

Name HAROLD ESTEP Address RR 7 - Box 120 Eugene, Ore.

(2) TYPE OF WORK (check):

New Well [] Deepening [x] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [x] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(5) CASING INSTALLED:

Threaded [] Welded [x]

6" Diam. from 62 ft. to 81 ft. Gage 250

(6) PERFORATIONS:

Perforated? [x] Yes [] No

Type of perforator used Miller Knife Size of perforations 7/8 in. by 3 in. 90 perforations from 18 ft. to 37 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 11 ft. below land surface Date 9/30/68 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [] No If yes, by whom? Bailer test 50 gal./min. with 25 ft. drawdown after 1 hrs. Temperature of water Was a chemical analysis made? [] Yes [] No

(10) CONSTRUCTION:

Well seal—Material used Depth of seal Diameter of well bore to bottom of seal Were any loose strata cemented off? [] Yes [] No Depth Was a drive shoe used? [] Yes [] No Did any strata contain unusable water? [] Yes [] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Lane Driller's well number 1/4 Section 12 T. 18S R. 3W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 4 ft. Depth drilled 20 ft. Depth of completed well 82 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include: Loose Sand & Gravel (62-66'), Cemented Sand & Gravel (66-72'), Loose Sand & Gravel (72-78'), Cemented Sand & Gravel (78-82').

Work started 9/24/68 Completed 9/30/68 Date well drilling machine moved off of well 9/30/68

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Frank Wilson Date 10/1, 1968 (Drilling Machine Operator)

Drilling Machine Operator's License No. 404

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME W.W. Phillips & Pump (Person, firm or corporation) (Type or print)

Address 2320 Main St. S.W. [Signed] Walt Wilson (Water Well Contractor)

Contractor's License No. 268 Date 9/30, 1968