NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

STATE OF OREGON SEPE 5 1974 State Well No. 185/11W-20
(Please type or print) STATE ENGINEER Permit No. 19133

(1) OWNER:	(10) LOCATION OF WELL:	
Name John McCarty	County Lane Driller's well number	C/43/T
Address Rt.2 Box 500	1/4 1/4 Section 20 T. 18S R.	11W W.M.
Florence, Oregon	Bearing and distance from section or subdivision corne	er
(2) TYPE OF WORK (check):		
New Well 🗵 Deepening 🗌 Reconditioning 🗎 Abandon 🖂		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 47	ft.
Rotary Driven Domestic K Industrial Municipal		
Cable M Jetted L	Static level 6 ft. below land surface.	<del> </del>
Dug	Artesian pressure lbs. per square inch.	Date
CASING INSTALLED: Threaded   Welded E	(12) WELL LOG: Diameter of well below ca	sing 6
6" Diam. from0 ft. to35 ft. Gage250	Depth drilled 56 ft. Depth of completed well	-/
" Diam. from ft. to ft. Gage		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and strue and show thickness and nature of each stratum and a	
DEDEOD AUTONS.	with at least one entry for each change of formation. Rep position of Static Water Level and indicate principal wa	
PERFORATIONS: Perforated? □ Yes 및 No.		T
Type of perforator used	MATERIAL From	To SWL
Size of perforations in. by in.	Yellow clay 0	16
perforations from ft. to ft. to ft.	- 424) 524)	
perforations from ft. to ft.	Yellow clay 16	32
perforations from ft. to ft.	Gray sandstone 32	56
(7) SCREENS: Well screen installed?   Yes I No		<del></del>
the state of the s		
Manufacturer's Name Model No		
Diam, Slot size Set from ft, to ft.		+ + -
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes 【X No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		
" " " " " " " " " " " " " " " " " " "		
" " "	,	<u> </u>
gardina with 10 In deal wall and in the	77.	<u> </u>
Artesian flow g.p.m.	- A	<del></del>
perature of water Depth artesian flow encountered ft.	Work started 9/4/74 19 Completed 9	0/5/74 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	0/5/74 19
	Drilling Machine Operator's Certification:	
Well seal—Material used	This well was constructed under my direc	
the contract of the contract o	Materials used and information reported above best knowledge and belief	are true to my
Diameter of well bore to bottom of seal		9/10/7410
Number of sacks of cement used in well seal	(Drilling Machine Operator)	-
	Drilling Machine Operator's License No	310
Number of sacks of bentonite used in well seal		•
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of water lbs./100 gals.	This well was drilled under my jurisdiction a true to the best of my knowledge and belief.	nd this report is
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.		
Did any strata contain unusable water?   Yes T No	Name Corvallis Drilling Co. Inc. (Ferson, firm or corporation)	'ype or print)
Type of water? depth of strata	Address 3440 SW 3rd St. Corvallis, On	ce. 9 <b>5</b> 330
Method of sealing strata off	Man 1 VC	
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] (Water Well Contractor)	***************************************
	Contractor's License No. 560 Date 9/10	/74
Gravel placed from ft. to ft.	Contractor's License No	18
	Halame to Michael Anti-	CT+4F0F0