NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion. STATE OF OREGON Print CHEESE type or print)

State	Well	Νo	1	9	/;	w		6	
State		1	L	N	E	•	******	*******	•

(1) OWNER: EALEM. OREGON	(11) WELL TESTS: Drawdown is amount lowered below static is	wajen je ol is
Name Pleasant Hill School District #1	Was a pump test made? ⊠ Yes ☐ No If yes, by whom	
Address Rt. 2	Yield: 20 gal./min. with 160 ft. drawdov	
Creswell, Oregon	" " "	"
(2) LOCATION OF WELL:	" "	"
. ,	Bailer test gal./min. with ft. drawdo	own after hrs.
County Lane Driller's well number	Artesian flow g.p.m. Date	
1/4 1/4 Section 6 T. /9.5 R. / (L) W.M.	Temperature of water Was a chemical analysis	made? 🗌 Yes 🗶 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below ca	ising
	Depth drilled 200 ft. Depth of completed we	
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c	l and structure, and the material in each hange of formation.
	MATERIAL	FROM TO
(3) TYPE OF WORK (check):	Sand & gravel	0 25
Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	Sand & gravel cemented	25 32
In abandonment, describe material and procedure in Item 12.	Bedrock	32 35
(A) DRADAGED TIGE (cheele). (E) MYDE OF WELL.	Bedrockblue	35 55
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Bedrockblue. sticky	55 65
Domestic M industrial Municipal Cable 初 Jetted 口	Grayish bedrock	65 70
Irrigation Test Well Other Dug Bored	Hard claygray	70 78
(6) CASING INSTALLED: Threaded Welded G	Hard bedrock	78 95
Timeaded Market	Blue bedrock	95 100
	Gray bedrock	100 150
" Diam. from ft. to ft. Gage	Gray clay & sand	150 160
" Diam, from ft. to ft. Gage	Redish grayish clay	160 180
(7) PERFORATIONS: Perforated? ☐ Yes ☑ No	Gray, sticky clay	180 200
Type of perforator used	Gray Soloky Gray	1 200
Size of perforations in. by in.		1
perforations from ft. to ft.	, , , , , , , , , , , , , , , , , , , ,	
perforations from ft. to ft.		
perforations from ft. to ft.	A PART OF THE PART	
perforations from ft. to ft.		
perforations from ft. to ft.		
(0) COPERIC	: :	
(8) SUREENS: Well screen installed? ☐ Yes ☐ No		
Manufacturer's Name		
Model No.		<u></u>
Dram Slot size Set from ft. to ft.	Work started 7/2/65 19 Completed	7/24/65 19
Diam Slot size Set from ft. to ft.		/24/65 19 -
(9) CONSTRUCTION:	(13) PUMP:	
	(25) 2 5222	
Well seal—Material used in seal Puddled clay & cement	Manufacturer's Name	. *************************************
Depth of seal ft. Was a packer used?	Type:	H.P
Diameter of well bore to bottom of sealin.	Water Well Contractor's Certification:	
Were any loose strata cemented off? Tyes Yes No Depth		
Was a drive shoe used? ★ Yes No	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this report is
Was well gravel packed? ☐ Yes [ĂNo Size of gravel:	trac to the best of my knowledge and beller.	
Gravel placed from ft. to ft.	NAME Casey Jones Well Drilling (
Did any strata contain unusable water? 🗌 Yes 🛛 No	1 · · · · · · · · · · · · · · · · · · ·	pe or print)
Type of water? depth of strata	Address Rt. 2 Box 695, Creswell,	redou
Method of sealing strata off	Drilling Machine Operator's License No423	
(10) WATER LEVELS:	(/) Man A A	
04.44.1	[Signed] July July Contractor	
Static level 20 ft. below land surface Date 7/24/65	(Water Well Contractor)	
Artesian pressure lbs. per square inch Date	Contractor's License No. 103 Date 8/26/	<u>55 , 19 </u>