NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, WATER RESOURCES DEPARTMENT,

SALEM, OREGON 97310 within 30 days from the date

-AUGO 7 1980Please type or print)

020505

WATER RESOURCES DEPT of well completion.

State Well No. $19s3\omega-14$
State Well 140.
State Permit No.

(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:		
Name City of Creswell	County James Driller's well number		
Address 2nd Street	1/4 1/4 Section 14 T. 195 R. 3W W.M.		
Creswell, OR 97426	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well 🗗 Deepening 🗌 Reconditioning 🗍 Abandon 🗍			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 36 ft.		
Potary Driven Domestic Industrial Municipal			
Drig Bored I Irrigation Test Well Other	,		
Dag Dorea Integration Less wen June	Artesian pressure lbs. per squar	e inch. Date	· · · · · · · · · · · · · · · · · · ·
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well by	olow enging	****
10 " Diam. from + 1 ft. to 130 ft. Gage 250	Depth drilled 130 ft. Depth of completed well 130 ft.		
	Formation: Describe color, texture, grain size and structure of materials;		
"Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
(6) PERFORATIONS: Perforated? Pryes 17 No.			
Type of perforator used SAW	MATERIAL	From T	ro swl
Size of perforations % in. by 3 in.	100 Soil	0 6	-,-
2500 perforations from 40 ft. to 120 ft.	Bat Run	6 21	
perforations fromft. toft.	Love Graval Bolates	35 40	
perforations fromft. toft.	Camantel Graves	40 5	
(7) SCREENS: Well screen installed? Yes You	Sand browal	55 5	
Manufacturer's Name	Camentee Esperal	57' 9.	
Type	Blue Sand & Craval	95 10	
Diam. Slot size Set from ft. to ft.	Blue clay	102 110	
Diam. Slot size Set from ft. to ft.	Blue Rock	110' 13	0 10
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
<u> </u>		 	
a pump test made? W Yes D No If yes, by whom? W W Orillary	- DEPENTER	 	
rield: 36gcm gal./min. with 102 ft. drawdown after 6 hrs.			
" " "	infar 2 - 2 1980	 	
H H H			
er test gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT		
g.p.m.	SALEM, OREGON		-
Temperature of water Depth artesian flow encountered	Work started /2/7 1979 Complete	ed 12	128 1978
(A) CONTENT OF THE CO	Date well drilling machine moved off of well		2 8 19 78
(9) CONSTRUCTION:	Date well drilling indexine moved out of well		2 6 100 7
Well seal—Material used	Drilling Machine Operator's Certification:	3!4	
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore to bottom of seal	best knowledge and belief.		
Diameter of well bore below sealin. Number of sacks of cement used in well seal sacks	[Signed] — How Wilson Date 12/28, 1979 (Drilling Machine Operator)		
Number of sacks of cement used in well seal sacks How was cement grout placed?	Drilling Machine Operator's License No. 404		
Lyo			
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? Yes PNo Plugs Size: location ft.	true to the best of my knowledge and belief. Name W.W. DRILLING-PUMP SALES & SERV. INC.		
Did any strata contain unusable water? Yes No	Name W. W. Drilling-Popp Sales & Serv. INC. (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 2320 Main St. Spfd. OR 97477		
Method of sealing strata off	2. 11.9		
Was well gravel packed? Yes No Size of gravel: 14 3	[Signed] / Control (Water Well Control	actor)	
20 120			F, 1979
Gravel placed from	Contractor's License No.		, 19