

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

LANE
020508

State Well No. 195/34-14

State Permit No.

RECEIVED
DEC 16 1975

(1) OWNER:

Name City of Cre
Address WATER RESOURCES DEPT.
SALEM, OREGON 97315

(10) LOCATION OF WELL:

County Lane Driller's well number
NE 1/4 NE 1/4 Section 14 T. 19S R. 3W W.M.
Bearing and distance from section or subdivision corner

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
16 " Diam. from +1 ft. to 31 ft. Gage 250
8 " Diam. from +1 ft. to 147 ft. Gage 250
" Diam. from _____ ft. to _____ ft. Gage _____

PERFORATIONS:

Perforated? Yes No.
Type of perforator used Torch
Size of perforations 1/4 in. by 6 in.
640 perforations from 40 ft. to 127 ft.
perforations from _____ ft. to _____ ft.
perforations from _____ ft. to _____ ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name _____
Type _____ Model No. _____
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered _____ ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 30 ft.
Diameter of well bore to bottom of seal 20 in.
Diameter of well bore below seal 14 in.
Number of sacks of cement used in well seal 40 sacks
Number of sacks of bentonite used in well seal _____ sacks
Brand name of bentonite _____
Number of pounds of bentonite per 100 gallons
of water _____ lbs./100 gals.
Was a drive shoe used? Yes No Plugs _____ Size: location _____ ft.
Did any strata contain unusable water? Yes No
Type of water? _____ depth of strata _____
Method of sealing strata off _____
Was well gravel packed? Yes No Size of gravel: 3/8
Gravel placed from 6.6 ft. to 15.5 ft.

(11) WATER LEVEL: Completed well.

Depth at which water was first found 18 ft.
Static level 6 ft. below land surface. Date 1/28/76
Artesian pressure _____ lbs. per square inch. Date _____

(12) WELL LOG:

Diameter of well below casing 14
Depth drilled 155 ft. Depth of completed well 147 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	2	
Clay Sand & gravel	2	14	
Sand & gravel	14	20	
Clay yellow & sand	20	45	
Sand Gravel & clay	45	100	
Broken clay	100	110	
Blue Rock	110	155	6

Work started 1/24 19 75 Completed 1/28 19 75
Date well drilling machine moved off of well 1/28 19 75

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Frank Wilson Date 1/28 19 75
(Drilling Machine Operator)
Drilling Machine Operator's License No. 404

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name W.W. Drilling & Pumping Ser. (Type or print)
(Person, firm or corporation)
Address 2320 Main St. S.W. Salem, Ore. 97317
[Signed] Frank Wilson
(Water Well Contractor)
Contractor's License No. 562 Date 1/28 19 75