The original and first copy of this report are to be filed with the JAN 101974 STATE OF OREGON JUL 2 1973state Well No. \_\_\_\_\_\_\_

STATE ENGINEER, SALEM, OREGON 97310 Within 30 days from the date STATE ENGINEER (Please type or prints TATE ENGINEER of well completion.

SALEM, OREGON not write above this line SALEM, OREGON OREGON.

(1) OWNER:	(10) LOCATION OF WELL: $020868$
Name DORSEY FICH	County have Driller's well number
Address 34823E DANSTROM R.F.	SE 145E 14 Section 26 T. 195R. 3W W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well   Deepening □ Reconditioning □ Abandon □ □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 50 ft.
Rotary Driven Domestic Industrial Municipal	Static level ft. below land surface. Date 6/25/17
Cable	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing
8 " Diam. from 6 ft. to 20 ft. Gage 250	
	Depth drilled / 33 ft. Depth of completed well / 3 5 ft.
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated?	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	10PS011 0 2
perforations from ft. to ft.	C/AX + GRAVE! 2 12
perforations from ft. to ft.	Blue Bock 12 135 5
perforations from ft. to ft.	
(7) SCREENS: Well screen installed?   Yes INO	
Manufacturer's Name	the second of th
Type Model No	- <del>-</del>
Diam. Slot size ft. ft. to ft.	
Diam Slot size Set from ft. to ft.	े प्रमुख्या ६८०० का
(8) WELL TESTS. Drawdown is amount water level is	<u> </u>
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	100
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	<u> </u>
<i>"</i> " " " " " " " " " " " " " " " " " "	
" " "	
Bailer test (200 gal./min. with 130 ft. drawdown after / hrs.	
Artesian flow g.p.m.	
Temperature of water Depth artesian flow encountered ft.	Work started 6/22 1973 Completed 6/23 1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6/23 19
O ement	Drilling Machine Operator's Certification:
Well seal—Material used	This well was constructed under my direct supervision.
1.7	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore to bottom of sealin.  Diameter of well bore below sealin.	2. 1) 12/1/2/1/2 - 1/n= -73
1 27	[Signed] (Drilling Machine Operator) Date (1.2.5), 19.
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No
Number of sacks of bentonite used in well seal sacks	
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water?  Yes No	Name (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 2320 MAIN ST
Method of sealing strata off	t louili-
	[Signed] (Water Well Contractor)
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	
Gravel placed from ft. to ft.	Contractor's License No. 562 Date 6/25 1973