

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy  
of this report are to be  
filed with the

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

STATE ENGINEER, SALEM, OREGON 973  
within 30 days from the date  
of well completion.

LANE  
020869

RECEIVED  
MAY 25 1973  
STATE ENGINEER  
SALEM OREGON

State Well No.

195/3W-26 dd

State Permit No.

(1) OWNER:

Name DORSEY FICH  
Address 34823E DANSTROM RD.  
CRISWELL, ORE

(2) TYPE OF WORK (check):

New Well  Deepening  Reconditioning  Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary  Cable  Driven  Jetted  Bored

(4) PROPOSED USE (check):

Domestic  Industrial  Municipal  Irrigation  Test Well  Other

(5) CASING INSTALLED:

Threaded  Welded   
6" Diam. from 0 ft. to 219 ft. Gage 250  
" Diam. from ft. to ft. Gage  
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated?  Yes  No

Type of perforator used

Size of perforations in. by in.  
perforations from ft. to ft.  
perforations from ft. to ft.  
perforations from ft. to ft.

(7) SCREENS:

Well screen installed?  Yes  No

Manufacturer's Name  
Type Model No.  
Diam. Slot size Set from ft. to ft.  
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made?  Yes  No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.  
" " " "  
" " " "  
Blow down test 25 gal./min. with 162 ft. drawdown after 1 hrs.  
Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement  
Well sealed from land surface to 19 ft.  
Diameter of well bore to bottom of seal 10 in.  
Diameter of well bore below seal 6 in.  
Number of sacks of cement used in well seal 3 sacks  
Number of sacks of bentonite used in well seal sacks  
Brand name of bentonite  
Number of pounds of bentonite per 100 gallons  
of water lbs./100 gals.  
Was a drive shoe used?  Yes  No Plugs Size: location ft.  
Did any strata contain unusable water?  Yes  No  
Type of water? depth of strata  
Method of sealing strata off  
Was well gravel packed?  Yes  No Size of gravel:  
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County LANE Driller's well number  
SE 1/4 SE 1/4 Section 26 T. 195 R. 3W W.M.  
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 100 ft.  
Static level 13 ft. below land surface. Date 5/10/73  
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 175 ft. Depth of completed well 175 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	1	
CLAY & Boulders	1	13	
BLUE SANDSTONE	13	95	
GRAY SANDSTONE	95	175	13

Work started 5/10 1973 Completed 5/10 1973  
Date well drilling machine moved off of well 5/11 1973

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Frank Wilson Date 5/11, 1973  
(Drilling Machine Operator)

Drilling Machine Operator's License No. 813

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name W.W. DRINKING  
(Person, firm or corporation) (Type or print)

Address 2320 MAIN SPRINGFIELD  
ORE

[Signed] Frank Wilson  
(Water Well Contractor)

Contractor's License No. 562 Date 5/72, 1973