NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

RECEIVED WATER WELL REPORT SEP 2 5 1974 State Well No.

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the data

021043 of well completion.

(Please type or print) STATE ENGINEER

(Do not write above this line SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Percy R. Cline	County Lane Driller's well number
Address Box 125, Creswell, Oregon 97426	34 14 Section 13 T. 19S R. 4W W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) TYAMED LEVIEL. Convoluted well
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 0 ft.
Rotary 🕃 Driven 🗌 Domestic 🏿 Industrial 🗎 Municipal 🗀 Cable 🔲 Jetted 🗍	Static level O ft. below land surface. Date
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded \(\begin{array}{cccccccccccccccccccccccccccccccccccc	(12) WELL LOG: Diameter of well below casing 6". Depth drilled 220 ft. Depth of completed well 220 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
	MATERIAL From To SWL
Type of perforator used	W. S.
Size of perforations in. by in.	Top Soil 2 7
perforations from ft. to ft.	
perforations fromft. toft.	itedation in our orange
perforations from ft. to ft.	DIOWII GOLD
(7) SCREENS: Well screen installed? ☐ Yes 💆 No	Blue Cong. 64 220
Manufacturer's Name	
Type Model No	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ☒ No If yes, by whom?	
eld: gal./min. with ft. drawdown after hrs.	3
" " "	
Thursday 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Tested by air, estimate could fluctuate "	
Egier test O gal./min. with O ft. drawdown after O hrs.	- 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Artesian flow g.p.m.	
mperature of water Depth artesian flow encounteredft.	Work started 9/12/74 19 Completed 9/13/74 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 9/13/74 19
Well seal—Material used Cement Well sealed from land surface to 59 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 6 in. Number of sacks of cement used in well seal 12 sacks Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed]
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Casey Jones Well Drilling Co., Inc.
Did any strata contain unusable water? 🗌 Yes 🛛 No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Rt 8 Box 695 Pleasant Hill, Oregon
Method of sealing strata off	[Signed] Casey I Ames
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 559 Date 9/13/74 , 19
	The state of the s