

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

RECEIVED
JUL 26 1972
STATE OF OREGON
WATER WELL REPORT
LANE
021984

State Well No. 20S/3W-10

STATE ENGINEER, SALEM, OREGON (Type or print)
within 30 days from the date
of well completion. SALEM OREGON (Do not write above this line)

State Permit No. G-7300?

(1) OWNER:

Name Jim Hart
Address PO Box 316
Cottage Grove, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

6" Diam. from 0 ft. to 30 ft. Threaded Welded Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" tested with air; estimate could fluctuate
pump test 40 gal./min. with 32 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement grout
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 14 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lane Driller's well number
1/4 1/4 Section 10 T. 20s R. 3W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 35 ft.
Static level 8 ft. below land surface. Date 7/18/72
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"
Depth drilled 50 ft. Depth of completed well 45 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
top soil	0'	2'	
brown soil	2	6	
brown clay & bolders	6	12	
brown clay gravel & boulders	12	26	
blue sand & gravel	26	45	
brown clay sand & gravel	45	50	

Work started 7/18/72 19 Completed 7/18/72 19
Date well drilling machine moved off of well 7/18/72 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] [Signature] Date July 19, 1972
(Drilling Machine Operator)

Drilling Machine Operator's License No. 702

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name CASEY JONES WELL DRILLING CO. INC.
(Person, firm or corporation) (Type or print)

Address Rt 8 Box 695 Pleasant Hill, Ore

[Signed] Casey L Jones
(Water Well Contractor)

Contractor's License No. 559 Date July 19, 1972