## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 9730 22022 STATE OF OREGON (Please type or print) STATE ENGINEER, SALEM, OREGON 9730 22022 STATE OF OREGON (Please type or print) STATE ENGINEER, SALEM, OREGON 9730 22022 STATE OF OREGON (Please type or print)

within 30 days from the date of well completion.

(Do not write above this line STATE ENGINEER Permit No. ....

	SALEM OREGON	
(1) OWNER:	(10) LOCATION OF WELL:	
Name Ivan Blood	County Iane Driller's well number 357	-
Address 370 1st Ave me West	SW 3WW 34 Section 17 T. 20S R. 3W	W.M.
Eugene, Oregon	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	and and another strongs products of the strongs of the strong	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):		
Rotanir El Dirition El	Depth at which water was first found	ft.
Cable	Static level 3 ft. below land surface. Date	120/7
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date	<u> </u>
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing	1"
	10-	<u> </u>
ft. Gage ft. Gage		ft.
ft. Gage	Formation: Describe color, texture, grain size and structure of n and show thickness and nature of each stratum and aquifer pe	
Annua I myoyg	with at least one entry for each change of formation. Report each	change in
PERFORATIONS: Perforated? Tyes Tho.	position of Static Water Level and indicate principal water-bearing	ng strata.
Type of perforator used	MATERIAL From To	swl
Size of perforations in. by in.	SOIL , 03	
perforations from ft. to ft.	BROWN CLAY 3/2	
perforations from ft. to ft.	BEDROCK / 12 35	<u> </u>
perforations from ft. to ft.	GRAY SANDSTONE MED 35 88	
(7) SCREENS: Well screen installed? \(\tau\) Yes	SANDSTONE HARD #88 125	57
Work Bostons Tribulation II was a factor	GERY SAXIDSTONE DARKA 125 125	75
Manufacturer's Name	RED CLAY 175 180	38
Type Model No		<del></del>
Diam.       Slot size       Set from       ft. to       ft.         Diam.       Slot size       Set from       ft. to       ft.		
Diditi Slot size Set Iron 1t. to 1t.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes ☐ No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		
" " " " " "		
" " "		
Bailer test 30 gal./min. with 92_ft. drawdown after / hrs.		
Artesian flow g.p.m.		
perature of water 2 Depth artesian flow encountered ft.	Work started 8/12 1973 Completed 8/28	197,
(A) CONCERNICATION	Date well drilling machine moved off of well	197 3
(9) CONSTRUCTION:	9,-0	
Well seal—Material used	Drilling Machine Operator's Certification:  This well was constructed under my direct super	
Well sealed from land surface toft.	Materials used and information reported above are true	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	
Diameter of well bore below sealin.	[Signed] Date H28	., 19.43
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 247	
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite YELLOWS TOME	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this r	eport is
of water 133 lbs./100 gals.	true to the best of my knowledge and belief.	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Miller-Jensen Company (Type or prin	-45
Did any strata contain unusable water?  Yes No	$P \cap Por 2E77 = France Or O71.03$	nt)
Type of water? depth of strata	Address 10 box 25/1 Eugene, 01 9/402	
Method of sealing strata off	DISTICUI	Owner
Was well gravel packed? Tyes No.—Size of gravel:	(Water Well Contractor)	-=-
Gravel placed fromft. toft.	Contractor's License 46, 179 Date 8-22-73	. 19