NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL RE

State Well No.

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGO

WHILE	(Please type or print)	-	CIVOI	A True your 6. "		
LAINE	C* 7 1	17	A ORE	State	Permit	N
CO O C 14Do	not write above this line)					

(1) OWNER:	(10) LOCATION OF WELL:						
Name EVANGEI CHURCH.	County Lane Driller's well number						
Address 1795 EAST Main CoHage Grow	14 14 Section 2 7 T. 20 R. 3 W.M.						
	Bearing and distance from section or subdivision corner						
(2) TYPE OF WORK (check):	s.aa.va.						
New Well Deepening Reconditioning Abandon							
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.						
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 3/ ft.						
Rotary Driven Domestic Mindustrial Municipal	Static level 2/ ft. below land surface. Date 3-22/13						
Cable Jetted Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date						
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well 1	oelow cas	sing	; x			
" Diam. from	Depth drilled 65 ft. Depth of completed well 65 ft.						
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size						
ft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in						
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal wa	ter-bearin	ig strata.			
Type of perforator used	MATERIAL	From	То	swL			
Size of perforations in. by in.	Sanp Conquel	25	6				
perforations from ft. to ft.	Sandy Clay 45/164	6	20				
perforations from ft. to ft.	Beb Center Ban	20	30				
perforations from ft. to ft.	FLACWB 1262/min	30	3/				
	Basolt HD	31	53				
(7) SCREENS: Well screen installed? Yes No	SHACWB 24 min	53	54	<u> </u>			
Manufacturer's Name	Black HD Basolt	54	65				
Type Model No							
Diam. Slot size Set from ft. to ft.							
Diam. Slot size Set from ft. to ft.							
(8) WELL TESTS: Drawdown is amount water level is		 					
lowered below static level				· · · · · · · · · · · · · · · · · · ·			
Was a pump test made? Yes No If yes, by whom?							
Yield: gal./min. with ft. drawdown after hrs.							
n n				 ;			
" /AIR " " "				·			
Batter test 24 gal./min. with 3/ft. drawdown after / hrs.							
Artesian flow g.p.m.	-			•			
erature of water 52 Depth artesian flow encountered ft.	Work started 3 22 19 13 Complete	ed. 3 -	22	19 2 3			
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3-2	3.3	19 23			
Well seal-Material used Cout Grout	Drilling Machine Operator's Certification:						
Well sealed from land surface to 25 BERTER Batt.	This well was constructed under my Materials used and information reported						
Diameter of well bore to bottom of seal	hest knowledge and belief.						
Diameter of well bore below sealin.	[Signed] H. D. Date 3-27, 19 13						
Number of sacks of cement used in well seal & SKC711 sacks	Drilling Machine Operator's License No. 338						
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's Elicense No.						
Brand name of bentonite	Water Well Contractor's Certification:			- - - - -			
Number of pounds of bentonite per 100 gallons		This well was drilled under my jurisdiction and this report is					
of water	true to the best of my knowledge and belief.						
Was a drive shoe used? Yes \square No Plugs Size: location ft.	Name (Person, firm or corporation) (Type or print)						
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print) Address BBR+BOX326 CH3Ge6100						
Type of water? depth of strata	Address DOUT DOUGLE		1.6.6	7.0.C.C			
Method of sealing strata off	[Signed] Holamury	,					
Was well gravel packed? ☐ Yes 📝 No Size of gravel:	(Water Well Cont						
Gravel placed from ft. to ft.	Contractor's License No. 421 Date	3 – <i>2</i>	2	, 19.23			
	·						