NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date of well completion.

LANE

WATER WELL REPORT

STATE OF OREGON
(Please type or print)
(Do not write above this line)

022409

RECEIVED
OCT 21 1977
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 20S/3W-32

State Permit No.

(1) OWNER:

Name Gorman Wright

Address 241 Talemena Drive
Cottage Grove, OR 97424

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒

6" Diam. from 0 ft. to 47½ ft. Gage .250

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " "

Tested by Air (Est. could fluctuate) "

Air 33 gal./min. with 90 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement

Well sealed from land surface to 96 ft.

Diameter of well bore to bottom of seal 10 in.

Diameter of well bore below seal 6 in.

Number of sacks of cement used in well seal 10 sacks

How was cement grout placed? Poured

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lane Driller's well number

¼ ¼ Section 32 T. 20S R. 3W W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 193 ft.

Static level 120 ft. below land surface. Date 8/24/77

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"

Depth drilled 210 ft. Depth of completed well 210 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	2	
Brown red clay	2	28	
Brownish yellow clay	28	42	
Brown claysotne	42	44	
Blue sandstone	44	76	
Green cong.	76	79	
Blue sandstone	79	83	
Blue green cong.	83	113	
Green cong.	113	127	
Blue brown cong.	127	136	
Blue green cong.	136	195	
Gray green cong.	195	210	

Work started 8/23 19 77 Completed 8/24 19 77

Date well drilling machine moved off of well 8/24 19 77

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] [illegible] (Drilling Machine Operator) Date 8/24, 19 77

Drilling Machine Operator's License No. 702

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Casey Joens Well Drilling Co., Inc.
(Person, firm or corporation) (Type or print)

Address 37115 Immigrant Road, Pleasant Hill, OR

[Signed] Casey F. Jones (Water Well Contractor)

Contractor's License No. 559 Date 8/24, 19 77

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119