NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

State Well No. 205

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON/UN1 2 1975

(Please type or print) STATE ENGINEER (Do not write above this line) SALEM, OREGON State Permit No.

(1) OWNED.	(10) LOCATION OF WELL:	
(1) OWNER:	County Lane Driller's well number	
Name Gorman Wright	34 14 Section 32 T. 20S R. 3W W.M	— ∓ Æ.
Address 241 Talemena Brive Cottage Grove, Oregon 97424	Bearing and distance from section or subdivision corner	_ =
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivision corner	- -,
	q _Q	
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐		_
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 91 f	it.
Rotary 🛮 Driven 🖸 Domestic 🖫 Industrial 🗍 Municipal 🗎	Static level 54 ft. below land surface. Date 5/24/7	<i>1</i> 5
Cable	Artesian pressure lbs. per square inch. Date	
CASING INSTALLED: Threaded Welded 2 Welded 2 So ft. Gage 250 ft. to ft. Gage 7 Diam. from ft. to ft. Gage 7 Diam. from ft. to ft. Gage 7 PERFORATIONS: Perforated? Yes X No.	(12) WELL LOG: Diameter of well below casing 6" Depth drilled 345 ft. Depth of completed well 345 f Formation: Describe color, texture, grain size and structure of materials and show thickness and nature of each stratum and aquifer penetrated with at least one entry for each change of formation. Report each change is position of Static Water Level and indicate principal water-bearing strategies.	a, in
Type of perforator used	MATERIAL From To SWL	
Size of perforations in. by in.	Top Soil 0 2	
perforations fromft. toft.	Red Brown Clay 2 10	
perforations fromft. toft.	Brown Clay 10 12	
perforations from ft. to ft.	Yellow Brown Clay 12 14	
periorations from	Light Brown & White Clay 14 21	
(7) SCREENS: Well screen installed? ☐ Yes ☒ No	Yellow Clay 21 38	
Manufacturer's Name	Yellow Brown Clay 38 45	_
Type Model No	Blueish Brown Sandstone 45 78	
Diam Slot size Set from ft. to ft.	Green Cong. 78 103	
Diam. Slot size Set from ft. to ft.	Blue Gray Cong. 103 290	—
(2) WFII TESTS. Drawdown is amount water level is	Red Cong. 290 327	_
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Blue Cong. 327 345	
Was a pump test made? ☐ Yes ☒ No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		_
" " "		
" "		
xBoxilexx text 8 gal./min. with 291 ft. drawdown after 1 hrs.		_
Artesian flow g.p.m.	Work started 5 /01 /75 19 Completed 5 /07 /75 19	
perature of water Depth artesian flow encountered ft.	Work stated 1/24/()	
(9) CONSTRUCTION:	Date wen drining machine moved of or men)/2///	
Well seal—Material used Cement Well sealed from land surface to 69 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 6 in. Number of sacks of cement used in well seal 13 sacks Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's Certification: This well was constructed under my direct supervisio Materials used and information reported above are true to n best knowledge and belief. [Signed] Oprilling Machine Operator) Drilling Machine Operator's License No. 702	ny
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons of water	This well was drilled under my jurisdiction and this report true to the best of my knowledge and belief.	is
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.	Name Casey Jones Well Drilling Co., Inc.	
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 37115 Immigrant Rd. Pleasant Hill, Oreg	;on
Method of sealing strata off	Consul of Consul	
	[Signed] (Water Well Contractor)	
Was well gravel packed? Yes No Size of gravel:	Contractor's License No	
Gravel placed from ft. to ft.	OTHERE OF THE OTHER	