## WATER WELL REPORT STATE OF OREGON

## RECEIVED

SEP 2 3 1981

LANE 1022428

	-	10	0	20	
State Well No.		900	$P^{\omega}$		

State Permit No.

WATER RESOURCES DEPT				
(1) OWNER: SALEM; OREGON	(10) LOCATION OF WELL:			
Name Gorman Wright	County Lane 'Driller's well number			
Address 241 Talemena	4 4 Section 32 T. 20S R. 3W W.M.			
City Cottage Grove State OR 97424	Tax Lot # Lot Blk Subdivision			
(2) TYPE OF WORK (check):	Address at well location:			
New Well ☑ Deepening □ Reconditioning □ Abandon □	(44) WARRED I DIVINE CO. L. L. J. J. J.			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 43 ft.			
Rotary Air 🛣 Driven 🗆 Domestic 🐹 Industrial 🗆 Municipal 🗆	Static level 1t. below land surface. Date 1/2 .			
Rotary Mud	Artesian pressure lbs. per square inch. Date			
□ Bored □ Thermal: Withdrawal □ Reinjection □	(12) WELL LOG: Diameter of well below casing 8"			
(5) CASING INSTALLED: Steel  Plastic  Particle  Property  Property	Depth drilled 300 ft. Depth of completed well 300 ft. Formation: Describe color, texture, grain size and structure of materials; and show			
Threaded □ Welded ☑ 8. "Diam from +1 ft to 30 ft Gauge 250	thickness and nature of each stratum and aquifer penetrated, with at least one entry			
	for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
LINER INSTALLED:				
•	MATERIAL From To SWL			
	Topsoil         0         1           Brown Clay         1         10			
(6) PERFORATIONS: Perforated? ☐ Yes ☒ No	Brown Clay         1         10           Clay Gravel         10         18			
Type of perforator used	Blue Gray Conglomerate 18 43			
Size of perforations in. by in.	Blue Claystone 43 57			
perforations from ft. to ft.	Purple Gray Conglomerate 57 110			
perforations from ft. to ft.	Gray Sandy Claystone 110 300			
perforations fromft. toft.				
(7) SCREENS: Well screen installed? ☐ Yes ☒ No				
Manufacturer's Name	<u> </u>			
Type Model No.				
Diam. Slot Size				
Diam. Slot Size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
s a pump test made?   Yes   No If yes, by whom?				
eld: gal./min. with ft. drawdown after hrs.	1 of collection (see			
Air test 20 gal./min. with drill stem at 300 ft. 1 hrs.				
Bailer test gal./min. with ft. drawdown after hrs.				
retesian flow g.p.m.  emperature of water Depth artesian flow encountered ft.				
	Work started 8-7 1981 Completed 8-13 1981			
(9) CONSTRUCTION: Special standards: Yes \( \text{No } \text{No } \text{No } \)	Date well drilling machine moved off of well 8–13 1981			
Well seal—Material used Portland Cement	Drilling Machine Operator's Certification:			
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.			
Diameter of well bore to bottom of seal	[Signard] Det 1/1 WMy Data 8-1319 81			
Number of sacks of cement used in well seal	(Drilling Machine Operator)			
How was cement grout placed?pressuregrouted	Drilling Machine Operator's License No			
now was cement grout placed?pl.eabut.egr.outdeu	Water Well Contractor's Certification:			
	This well was drilled under my jurisdiction and this report is true to			
Was pump installed?	the best of my knowledge and belief.			
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.	Name Casey Jones Well Drilling Co., Inc. (Person, firm or corporation) (Type or print)			
Did any strata contain unusable water? □ Yes ☒ No	Address 37115 Immigrant Rd Aleasant Hill, OR			
Type of Water? depth of strata	(1)			
Method of sealing strata off	[Signed] (Water Well Contractor)			
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	Contractor's License No. 559 Date 8-13 , 1981			
Gravel placed from ft. to ft.				