State Well No. 805	30	-32
--------------------	----	-----

NOTICE TO WATER WELL STATE OF THE ORIGINAL AND STATE ENGINEER, SALEM OF THE ORIGINAL EM ORIGINAL E

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:			
Name XX Gorman Wright	County Ine Driller's well number			
Address 917 Sweet Lane	14 14 Section 32 T. 20s	R. 3w W.M.		
Cottage Grove, Oregon	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	31			
New Well Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	30½ ft.		
Rotary Driven Domestic Lindustrial Municipal Cable Detted D	Static level 7 ft. below land :	surface. Date 8/2/72		
Dug Bored I Irrigation Test Well Other	Artesian pressure Ibs. per squar	re inch. Date		
CASING INSTALLED: Threaded Welded X 6 "Diam from O ft. to 30 ft. Gage 250 "Diam from ft. to ft. Gage "Diam from ft. to ft. Gage PERFORATIONS: Perforated? Yes No.	(12) WELL LOG: Diameter of well below casing 6". Depth drilled 290 ft. Depth of completed well 290 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
ype of perforator used	MATERIAL	From To SWL		
Size of perforations in. by in.	brown tap soil	0' 2'		
perforations from ft. to ft.	yellow clay	2 3		
perforations from ft. to ft.	brownish red clay	3 4		
perforations from ft. to ft.	gray clay	4 8		
(7) SCREENS: Well screen installed? Yes No	brown clay green clay 570//E	8 16		
Manufacturer's Name	green sandstone	18 56		
Type Model No	brown sandstone	56 58		
Diam Slot size Set from ft. to ft.	gray sandstone	58 123		
Diam Slot size Set from ft. to ft.	brown sandstone	123 128		
(8) WELL TESTS: Drawdown is amount water level is	grayblue sandstone	1281 193		
lowered below static level	light kray sandstone	193 225		
Was a pump test made? 🗌 Yes 💆 No If yes, by whom?	blue gray sandstone	225 268 268 272		
Yield: gal./min. with ft. drawdown after hrs.	brown sandstone blue gray sandstone	272 290		
1 " " " " " " " " " " " " " " " " " " "	orde Stal sauda tone	1616 670		
tested with air; estmate could fluctuate "				
gal./min. with 28 ft. drawdown after 1 hrs.	tg			
Artesian flow g.p.m.				
Temperature of water Depth artesian flow encountered ft.	Work started 8/1/72 19 Completed 8/2/72 19			
(J) CONSTRUCTION:	Date well drilling machine moved off of well	8/2/72 19		
Well seal—Material used Cement grout Well sealed from land surface to 20 ft.	Drilling Machine Operator's Certification: This well was constructed under my			
Well sealed from land surface to	Materials used and information reported above are true to my best knowledge and belief.			
Diameter of well bore below seal	1 1 1 2 9/2 70			
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)			
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 702			
Brand name of bentonite				
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes No Plugs Size: location ft.	NameCASEY_JONES_WELL_DRILLING_CO_INC			
Did any strata contain unusable water? Yes X No	(Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address Rt 8 Box 695 Fleasant High, Ore			
Method of sealing strata off	[Signed] Casey James			
Was well gravel packed? [] Yes [No Size of gravel:	(Water West Contractor) Contractor's License No559 Date Aug. 31972, 19			
Gravel placed from ft. to ft.	Contractor's License No	UK3419 19		