WATER WELL REPORT STATE OF OREGON

RECEIVE Le Well No. 20 78 SEP 2 1983 State Permit No. PLEASE TYPE or PRINT IN RESOURCES DEPT.

	GAY FM. OREGON
1) OWNER:	(10) LOCATION OF WELL:
Vame South LANE School Dist	County /ANE Driller's well number
Address 455 ADAMS	1/4 1/4 Section 33 T. 205 R. 3(1) W.M.
City Cottage Crewne State ORe 97424	Tax Lot # Lot Blk Subdivision
	Address at well location: Cottage Grave Highschas
2) TYPE OF WORK (check):	
New Well Deepening □ Reconditioning □ Abandon □	(11) WATER LEVEL: Completed well.
f abandonment, describe material and procedure in Item 12.	Depth at which water was first found 26, ft.
3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level /8 ft. below land surface. Date 7/22
Rotary Air Driven Domestic Industrial Municipal	Artesian pressure lbs. per square inch. Date
Rotary Mud Dug Irrigation Test Well Other Thermal: Withdrawal Reinjection	(12) WELL LOG: Diameter of well below casing
E) CACINIC INCOMIT FID.	Depth drilled /50 ft. Depth of completed well /50 ft.
5) CASING INSTALLED: Steel Plastic Welded Welded	Formation: Describe color, texture, grain size and structure of materials; and show
8. "Diam from + 2. ft. to 5. 7. ft. Gauge + 280	thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level
	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
"Diam. from ft. to ft. Gauge	TOPSOUL 02
(6) PERFORATIONS: Perforated? Yes \(\text{No}\) Type of perforator used	L+ Bann C/AY 2 15
Size of perforations //4 in. by //2 in.	
64 perforations from 23 ft. to 55 ft.	L+ Brown Sousstre (Soft) 15 38
perforations fromft. toft.	
perforations from ft. to ft.	BARRIN SANDSHOVE SAF 38 45
(7) SCREENS: Well screen installed? Yes X No	m/c 1 1 10 + 1 - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Manufacturer's Name	M/S combinerat & Tuff 43 65
Type	m/s Rho- GROY TUFF 65 150
Diam. Slot Size Set from ft. to ft.	mys see ceny 1011
Diam. Slot Size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
-11	
Was a pump test made? X Yes □ No If yes, by whom? School DS	
d: 47gal/min. with 60 ft. drawdown after 7 hrs.	
Air test 48 gal/min. with drill stem at 148 ft. 1 hrs.	
Air test 48 gal./min. with drill stem at 48 ft. hrs. Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 7/18 19 83 Completed 7/22 198
(9) CONSTRUCTION: Special standards: Yes \(\text{No } \)	Work started 7/13 19 83 Completed 7/2 1985 Date well drilling machine moved off of well 7/22 1985
Well seal—Material used Cement	(unbonded) Water Well Constructor Certification (if applicable):
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal	and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed]
Number of sacks of cement used in well sealsacks	Bonded Water Well Constructor Certification:
How was cement grout placed? Punp HARO Primit	Bond 5740-34-13 Issued by: TRANS HIVERIA
	(number) Surety.Company Name This well was drilled under my jurisdiction and this report is true to
Test Duen C.h. 2 - 100.	the best of my knewledge and belief.
Was drive chee word? Sys. No. Plums Size lection / ft.	Name Christensen West Lettering Co. (Type or print)
Was a drive shoe used?	Address 33/32 Coleman Ro, Eugene
Type of Water? depth of strata	Dich to 100
Method of sealing strata off	[Signed] Water Well Constructor
Was well gravel packed? XYes □ No Size of gravel:	Date8./20, 19.83
Gravel placed from	