

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

LANE WATER WELL REPORT RECEIVED

022842

STATE OF OREGON
(Please type or print)

State Well No. 20S 2E-35
FEB 23 1978

(Do not write above this line) WATER RESOURCES DEPT.
SALEM, OREGON

(1) OWNER:

Name Willamette National Forest
Address P.O. Box 10607
EUROPE, OREGON

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
" Diam. from 0 ft. to 40 ft. Gage 280
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Bailer test 8 gal./min. with 71 ft. drawdown after 2 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 11 sacks
How was cement grout placed? press grout.

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County LANE Driller's well number 12/78
¼ ¼ Section 35 T. 20S R. 2E W.M.

Bearing and distance from section or subdivision corner
SHady DELL CAMPground

(11) WATER LEVEL: Completed well.

Depth at which water was first found 80 ft.
Static level 10 ft. below land surface. Date 2/22/78
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Six
Depth drilled 95 ft. Depth of completed well 95 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
SOIL	0	2	
Sand & clay, blue w/ gravels.	2	35	
Sandrock, grey, hard	35	80	
Sandrock, yellow	80	81	10
broken water stratum			
Sandrock, grey	81	95	

Work started Feb 20 1978 Completed Feb 22 1978
Date well drilling machine moved off of well Feb 22 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Froy W. Mutschler Date 2/25, 1978
(Drilling Machine Operator)
Drilling Machine Operator's License No. 80

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name M-H Well Drilling Inc.
(Person, firm or corporation) (Type or print)
Address 735 N.W. Oak Creek Dr. Corv. Ore
[Signed] Froy W. Mutschler
(Water Well Contractor)
Contractor's License No. 237 Date Feb 25, 1978