NOTICE TO WATER WELL CONTRACTOR SEP 5 - WATER WELL REPORT

UANS tate Well No. 275/2E- 12b
02353 The Permit No.

state engineer, salem, oregon state ENCINGLE type or print) within 30 days from the date of well completion.

(1) OWNER:	(10) LOCATION OF WELL:
Name OAKRIDGE SCHOOL (RW)	County LANE Driller's well number 52028/22
Address OAKHIDGE, OREGON	34 NW 34 Section 12 T. 21 R. 2E W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 💢 Deepening 🗌 Reconditioning 🗍 Abandon 🗌	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found a 87 ft.
Rotary Driven Domestic M Industrial Municipal	Static level 14 ft. below land surface. Date 8-16-72
Cable K Jetted	Artesian pressure lbs. per square inch. Date
Dug	Artesian pressure ins. per square men.
CASING INSTALLED: Threaded □ Welded X	(12) WELL LOG: Diameter of well below casing $\frac{8}{100}$ $(7\frac{1}{4})$
8 " Diam. from 0 ft. to 22 ft. Gage .250	Depth drilled 97 ft. Depth of completed well 97 ft.
8 "Diam from 22 ft. to 49 ft. Gage 375	Formation: Describe color, texture, grain size and structure of materials;
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
THE PROPERTY OF THE PROPERTY O	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
PERFORATIONS: Perforated? Yes X No.	
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	SANDY TOP SOIL 0 4
perforations from ft. to ft.	LARGE BOULDERS 4 18
perforations from ft. to ft.	SAND, GRAVEL WITH LARGE COBBLES 18 44
perforations fromft, toft.	LIGHT BLUE SHALE 44 87
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	HARD GREY ROCK 87 97 14
Manufacturer's Name	HARD GREE AUGA
Type Model No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	4
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? [] Yes [] No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" "	
" " " "	Versit Alice Land Service Francisco
Bailer test 75 gal./min. with 36 ft. drawdown after 2 hrs.	The stage of the s
DARCE CEST / J Santy	
Artesian flow g.p.m.	Work started 8-5-72 19 Completed 8-17-72 19
erature of water 00 Depth artesian flow encounteredft.	WOLK BRIEFOR
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8-18-72 19
Well seal-Material used PORTLAND CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface to 49 ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal 14 in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal 8 in.	[Signed] MAUN Date 8-23-72, 19 Date 8-23-72, 19
Number of sacks of cement used in well sealsacks	· ¬••
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water lbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? 🕅 Yes 🖂 No Plugs Size: location ft.	Name CARTER'S DRILLING & PUMP SERVICE
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print) Address 325 So. 2ND ST. SPRINGFIELD, OREGON
Type of water? depth of strata	Address 525 505 ZND 512 SPRINGF TELD, GREGOR
Method of sealing strata off	[Signed] Lames L. (a.L.)
Was well gravel packed? ☐ Yes 🎇 No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 126 Date 8-23-72 , 19