WATER WELL REPORT-STATE OF OREGON

023607

REGEIVED

AUG 2 0 1982

No.	215/35-10	
	,	

WATER RESOURCES DEFT.

State Well No.	$\alpha - \gamma \omega \gamma \omega$
State Permit No.	

(1) OWNER:	(10) LOCATION OF WELL:		
Name Mormon Church	County Lane Driller's well number		
Address McFarland Road	4 4 Section 10 T. 21s R. 3e	W.M.	
<u>City Oakridge</u> State OR	Tax Lot # Lot Blk Subdivision		
(2) TYPE OF WORK (check):	Address at well location:		
New Well ⊠ Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
	Depth at which water was first found 75	ft.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 30 ft. below land surface. Date 7-	-27-	
Rotary Air X Driven Domestic Industrial Municipal X Potary Mud Dug Inrigation Test Well Other D	Artesian pressure lbs. per square inch. Date		
☐ Bored ☐ Thermal:Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below casing		
(5) CASING INSTALLED: Steel Plastic Plastic	Depth drilled 285 ft. Depth of completed well 285	ft.	
Threaded \square Welded \square	Formation: Describe color, texture, grain size and structure of materials; and	show	
6	thickness and nature of each stratum and aquifer penetrated, with at least one for each change of formation. Report each change in position of Static Water	entry	
"Diam. from ft. to ft. Gauge	and indicate principal water-bearing strata.	20.01	
LINER INSTALLED:	MATERIAL From To ST	WL	
	Red Brown Clay 1 17		
(6) PERFORATIONS: Perforated? ☐ Yes X No	Gray, Green, Brown Conglomerate 17 33		
Type of perforator used	Gray, Blue, Green Congomerate 33 70		
Size of perforations in. by in.	Green Conglomerate 70 132		
perforations fromft. toft.	Gray Green Conglomerate 132 215		
perforations fromft. toft.	Gray Green Sandstone 215 285		
perforations from ft. to ft.			
(7) SCREENS: Well screen installed? ☐ Yes ☒ No			
Manufacturer's Name			
Type Model No.			
Diam. Slot Size Set from ft. to ft.			
Diam. Slot Size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
DOION BOARD ROVEL			
s a pump test made? Yes No If yes, by whom?			
Aeld: gal/min. with ft. drawdown after hrs. """"""""""""""""""""""""""""""""""""			
Bailer test gal./min. with ft. drawdown after hrs. tesian flow g.n.m.			
Temperature of water Depth artesian flow encountered ft.			
(O) CONCERNICATION		<u>982</u>	
(9) CONSTRUCTION: Special standards: YesX No □ Well seal—Material usedPortlandCement		19 <u>82</u>	
Well sealed from land surface to	Drilling Machine Operator's Certification:		
Diameter of well bore to bottom of seal 1Ω in.	This well was constructed under my direct supervision. Materials and information reported above are true to my best knowledge and be	used	
Diameter of well bore below seal			
Number of sacks of cement used in well sealsacks	Stopping .		
How was cement grout placed?pressuregrouted	Drilling Machine Operator's License No		
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is true	ue to	
Was pump installed?	the best of my knowledge and belief.		
Was a drive shoe used? ☆ Yes □ No Plugs	Name Casey Jones Well Drilling Co., Inc. (Person, firm or corporation) (Type or print)		
Type of Water? depth of strata	Address 37117 Immigrant Rd. Pleasant Hill, OR	•••••	
Method of sealing strata off	[Signed] (CASLY L Longs		
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	(Water Well Contractor)		
Gravel placed fromft. to	Contractor's License No559 Date	B2	