NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the WATER WELL REPORT

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date

STATE OF OREGON

WAR 1 1978 state Well No. @

of well completion.

(Please type or print) TERSOURCES State Premit No. (Do not write above this line) JALEM. OREGON*

(1) OWNER:	(10) LOCATION OF WELL:			
Name WILLAMOTTE NATIONAL Forest	County LANC Driller's well n	umber	13/	78
Address P.O. Box 10607 EUGENE, OREGON	SE 45E 4 Section // T. 245	R. :	3 E	W.M.
<u> </u>	Bearing and distance from section or subdivis		er	
(2) TYPE OF WORK (check):	CAMPERS FLAT CAMPAROUND			
New Well Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	1	3		٠
Rotary Driven D	0.1:			In the
Cable	Static level 8.6/11 ft. below land	surface.	Date 4	29/18
Dug Bored Irrigation Test Well Other	Artesian pressure Ibs. per squa	re inch.	Date	•
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well		<-	: 1
" Diam. from 0 ft. to 2/ ft. Gage 280	A /			<u></u>
"Diam. fromft. toft. Gage	Depth drilled //3 ft. Depth of comp			ft.
	Formation: Describe color, texture, grain size	and stru	cture of	materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in			
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	icipal wa	ter-beari	ng strata.
Type of perforator used	MATERIAL	From	То	swL
Size of perforations in. by in.	Soil.	0	3	
perforations fromft. toft.	SANdrock, brown	3	13	-
perforations fromft. toft.	" blue	13	16	
perforations fromft. toft.	11 proud	16	26	,
	BASALT, BLACK	26	43	8.6
(7) SCREENS: Well screen installed? Yes No	SANdrock, brown W/QTZ	43	48	
Manufacturer's Name	BASALF, BLACK	48	61	-
Type Model No.	SAndrock , brown w/012	61	63	
Diam Slot size Set from ft. to ft.	BASALT, DIACK	63	67	
Diam ft. to ft.	SANdrock Soft blue	67	80	
	Cong. RED, blue, black	80	84	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	SANdrock, grey	84	93	
Was a pump test made? [] Yes [No If yes, by whom?	BASALF, BIACK	93	115	
Yield: gal./min. with ft. drawdown after hrs.				
" " "				
	SMALL broken water			-
Dit	Stratum At	43		
Bailer test gal./min. with a / ft. drawdown after hrs.	<u> </u>			
Artesian flow g.p.m.				
perature of water Depth artesian flow encountered ft.	Work started Feb 23 1978 Complete	ed Fel.	524	1923
(9) CONSTRUCTION:	Date well drilling machine moved off of well	<u>Fob</u>	25	1973
Well seal—Material used Cement	Drilling Machine Operator's Certification:			
Well sealed from land surface to 20 ft.	This well was constructed under my	direct		
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above	are true	e to my
Diameter of well bore below sealin.	TOOM (IN LATERAL)	5. 7	2/25	22
Number of sacks of cement used in well seal	(Drilling Machine Operator)			
How was cement grout placed? Tress grout	Drilling Machine Operator's License No. 80			
	Water Well Contractor's Certification:	'		· '
The state of the s	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? 🗌 Yes 🗹 No Plugs Size: location ft.	Name MH WILL DRILLING.			
Did any strata contain unusable water? Yes No	(Person, firm or corporation)			nt)
Type of water? depth of strata	Address 1535 N.W. CAK Creek D	r. 601	RV. C	Re
Method of sealing strata off	Town I Lenous his Men In	Klos	. >	
Was well gravel packed? ☐ Yes W No Size of gravel:	[Signed] (Water Well Control	actor)	····	
Gravel placed from ft. to ft.	Contractor's License No. 237 Date 1	26-1	25	, 198