Lane RECEIVED

STATE OF OREGON	52262	WELL I.D.#	<u>L04343</u>	APR 2 2 1997	
WATER SUPPLY WELL (as required by ORS 537.765)	REPORT			FER RESOURCES DEPT.	0
Instructions for completing thi	s report are on the la	st page of this form.	WAT	FER RESOURCES DEPT.	
4) OHNED	***			SALEM, OREGON	

This action of compressing and report and all pages	SALEM, OREGON					
(1) OWNER: Well Number	(9) LOCATION OF WELL by legal description:					
Name Jaff Chastain	County Latitude Longitude					
Address 90241 Hwy 101 N.	Township 17 S N or S Range 12 W E or W. V	WM.				
City Florence State DR Zip97439	Section 22 NE 1/4 NE 1/4					
(2) TYPE OF WORK	Tax Lot 200 Lot Block Subdivision					
New Well Deepening Alteration (repair/recondition) Abandonment	Street Address of Well (or nearest address) 90241 Hwy 101	$\bot N$				
(3) DRILL METHOD:	Florence, or					
Rotary Air Rotary Mud Cable Auger	(10) STATIC WATER LEVEL:					
Other	ft. below land surface. Date 3/24	97				
(4) PROPOSED USE:	Artesian pressure lb. per square inch. Date					
Domestic Community Industrial Irrigation	(11) WATER BEARING ZONES:					
Thermal Injection Livestock Other						
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first found					
Special Construction approval Yes No Depth of Completed Well 250 ft.						
Explosives used Yes No Type Amount	From To Estimated Flow Rate	SWL				
HOLE SEAL	140 148 2	68				
Diameter From To Material From To Sacks or pounds	175 250 +3	68				
10" 0' 74' Coment w/ 47 0 74' 28						
botonite						
6" 74' 250						
	(14) MIELT LOC.					
How was seal placed: Method A B C D E	(12) WELL LOG: Ground Elevation					
	Giodila Elevation					
Backfill placed from ft. to ft. Material	Material From To S	WL				
Gravel placed from ft. to ft. Size of gravel	Topso:\\ 0 2					
(6) CASING/LINER:	Rown clay 2 7					
• •						
Cusing C =						
	Brown Sandstone 32 48 Grow Sandstone soft 48 65					
		්ත්				
		& &				
Liner: 4" 10' 250 1600		8				
	Bray sandstone 160 250 6	20				
Final location of shoe(s)						
) (7) PERFORATIONS/SCREENS:						
Perforations Method drill 3/2"						
Slot Type Material Tole/pipe						
From To size Number Diameter size Casing Liner						
50 110 36 3/8						
125 140 17 3/8	3 shale traps @					
150 195 47 318	125, 150, 210					
210 250 40 3/8						
	700 00 00 00 00					
(8) WELL TESTS: Minimum testing time is 1 hour	Date started 3 25 97 Completed 3 27 97					
well output may fluctuateFlowing	(unbonded) Water Well Constructor Certification:					
Pump Bailer Artesian	I certify that the work I performed on the construction, alteration, or abando of this well is in compliance with Oregon water supply well construction stand					
Yield gal/min Drawdown Drill stem at Time	Materials used and information reported above are true to the best of my know					
5 182 250 1 hr.	and belief.					
	WWC Number					
	SignedDate					
Temperature of water 51° Depth Artesian Flow Found	(bonded) Water Well Constructor Certification:					
Was a water analysis done? Yes By whom	I accept responsibility for the construction, alteration, or abandonment work					
Did any strata contain water not suitable for intended use? Too little	performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well					
Salty Muddy Odor Colored Other	construction standards. This report is true to the best of my knowledge and belief.					
Depth of strata:	WWGNumber 636					
-	Signed Call Musterse Vthe Date					

ORIGINAL & FIRST COPY-WATER RESOURCES DEPARTMENT SECOND COPY-CONSTRUCTOR THIRD COPY-CUSTOMER Christensen well Onling Co.