1979 lease type or print) STATE ENGINEER, SALEM, OREGON 97310 Col State Permit No. within 30 days from the date (Do not write above this line) of well completion. SOURCES DEPT SALEM, OREGON (10) LOCATION OF WELL: (1) OWNER: Driller's well number 4 - 26 - 79 County LANE RANGH Name LANE SW 145E 14 Section 29 T./6-5 R.3-W STALLING Address 9/28/ EUGENE Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Wel Deepening Abandon [7] Reconditioning [If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): Depth at which water was first found (3) TYPE OF WELL: Static level 14 ft. below land surface. Date 7 Driven [] Rotary Domestic D Industrial D Municipal D Jetted [Cable Irrigation Test Well Other lbs. per square inch. Date Artesian pressure Bored [] (5) CASING INSTALLED: Threaded | Welded (12) WELL LOG: Diameter of well below casing ... 8 "Diam from +1 tt to 2.76 st. Gage , 2.50 308 ft. Depth of completed well Depth drilled " Diam, from ft. to ft. Gage Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, ft. to ft. Gage " Diam. from with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. Perforated? Yes DNo. (6) PERFORATIONS: From MATERIAL Type of perforator used MILLS KNIFE TOP SUIL 3/8 in. by Size of perforations SAND 4 GRAVEL WITH CLAY 6 29 40 perforations from ... SANDAGRAVEL - LOOSE 40 perforations from 48 n SAND + GRAVEL WITH CLAY-TIGHT 1.7 25 perforations from 14 25 SAND + GRAVEL - LOOSE 10 104 29 M No SAND + GRAVEL WITH CLAY-TIGHT 3 (7) SCREENS: Well screen installed? SAND & SMALL GRAVEL - LOCSE SAND + GRAVEL WITH CLAY-TIGHT M. SAND + SMALL GRAVEL - LOOSE 6 S Diam. Slot size Set from 74 MSAND + GRAVEL WITH CLAY-TIGHT 101 Diam. Slot size Set from 101 104 LOOSE SAND Drawdown is amount water level is lowered below static level (8) WELL TESTS: 104 LOOSE SAND & SMALL GRAVEL 108 Was a pump test made? MYes DNo If yes, by whom? DRILLER CLAY WITH SAND & GRAVEL SET 108 LOOSE SAND 110 gal./min. with 51 ft. drawdown after SAND + SMALL GRAVEL 11.7 BLUE CLAY - SOFT 119. 158 BROWN CLAY + GRAVEL - SOFT 173. ft. drawdown after BLUE GREEN CLAY - SOFT hrs. gal./min. with Bailer test g.p.m. Artesian flow 19.79 Completed asm Temperature of water 58 Depth artesian flow encountered Work started + 26, Date well drilling machine moved off of well (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used CEMENT This well was constructed under my direct supervision. Materials used and information reported above are true to my Well sealed from land surface to best knowledge and belief. Diameter of well bore to bottom of seal .. [Signed] Clayton Haar Date 5 3 1974 Diameter of well bore below seal in. (Drifting Machine Operator) Drilling Machine Operator's License No. 489 Number of sacks of cement used in well seal Number of sacks of bentonite used in well seal ... Water Well Contractor's Certification: Brand name of bentonite Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is lbs./100 gais. true to the best of my knowledge and belief. Name CLAYS WELL DRILLING(Person, firm or corporation) (Type or print) Was a drive shoe used? Yes | No Plugs Size: location ... ft. Did any strata contain unusable water? Yes No Address 91467 STALLING LANE depth of strata Type of water? [Signed] Clayton Haar Method of sealing strata off Was well gravel packed? [] Yes No Size of gravel: Contractor's License No. 502 Date May Gravel placed from

REPORT

LANE 59199

The original and first copy

of this report are to be filed with the