NOTICE TO WATER WELL CONTRACTOR

The original and first conv.

of this report are to be The original and first cony of this report are to be filed with the

STATE ENGINEER, SALEM OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT CEIVED WELL NO. 155 4W 8

(Do not write above this line) RESOURCES DEPT.

(Please type or print) NOV 8 1976 State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	, , , , , , , , , , , , , , , , , , , ,	
Dormand Toman	· · · · · · · · · · · · · · · · · · ·	mber C/41/L	
Address 28645 Jager L ane	10 15	Azur	
Junction City, Ore. 97448			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on corner	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		- · · · · · · · · · · · · · · · · · · ·	
If abandonment, describe material and procedure in Item 12			
	(11) WATER LEVEL: Completed w	ell.	
	Depth at which water was first found	22 ft.	
Rotary Driven Domestic Industrial Municipal S	Static level 6 ft. below land s	urface. Date 10/27/7	
Durg Cl Borned Cl Impigation Cl Most Well At Other	Artesian pressure lbs. per squar		
CASING INSTALLED: Threaded □ Welded ★ 10." Diam. from 0 ft. to 40 ft. Gage 250	(12) WELL LOG: Diameter of well below casing 10 Depth drilled 44 ft. Depth of completed well 44 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in		
Type of perforator used Torch cut	MATERIAL	From To SWL	
Size of perforations 1/4 in. by 4 in.	Topsoi1	0 3	
320 perforations from 22 ft. to 37 ft.	Sand&gravel	3 37	
perforations fromft. toft	Brown clay	37 44	
perforations from ft. to ft			
	, *		
(7) SCREENS: Well screen installed? ☐ Yes 🗷 No			
Manufacturer's Name			
Type Model No.			
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	3-		
Yield: gal./min. with ft. drawdown after hrs.			
" " " " " " " " " " " " " " " " " " " "			
" tested with gir could fluctuate "	12. 1		
7 January 500 18 18 11 18 18	Article Control of the Control of th		
A-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	A STATE OF THE STA		
perature of water Depth artesian flow encountered ft.	Work started 10/27/76 19 Complete		
(b) Constitution.	Date well drilling machine moved off of well	11/1/76 19	
The state of the s	Drilling Machine Operator's Certification:	31	
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	above are true to my	
Diameter of well bore to bottom of sealin_ b	pest knowledge and belief		
Diameter of wen bore below sear	Signed] Donald 150 me I	Date 11/3/76 19	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 1043		
- BUCKS	Firming Machine Operator's Incense Mo.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is		
of water	true to the best of my knowledge and belief.		
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ☐ No	Name Corvallis Drilling Co. Inc.		
	(Person, firm or corporation) 3440 SW 3rd. Corvallis Ore.		
	Address Handle Conversion		
Method of sealing strata off	[Signed] Claud of Kingly		
Was well gravel packed? ☐ Yes ▼ No Size of gravel:	(Water Well Contractor)		
Gravel placed from ft. to ft. C	Contractor's License No560 Date	1/3/76 , 19	