NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

LANE 6/59 State Well No.

The original and first copy of this report are to be filed with the

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON STATE SALEM, OR SALE

State Permit No. ... WIDL 149503

Water to the state of the state		
(1) OWNER:	(11) LOCATION OF WELL: Owrd rei	vesd per LANE 80118
Name Robert E. Bryson	County Lane Driller's well num	nber
Address 102 Lingo Lane, Junction City	14 14 Section 20 T. t 5	S R. 4W W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	corner
	29249 LINGO LANE JUNCTION CITY OR 97448	
New Well Deepening Reconditioning Abandon If abandonment, describe material and procedure in Item 12.	44.25600000 -123.19900000	
(3) TYPE OF WELL: (4) PROPOSED USE (check):		·
Rotary El Driven El	(12) WELL LOG: Diameter of well be	low casing6
Cable	Depth drilled 35 ft. Depth of complete	ted well 35 ft.
Dug	Formation: Describe color, texture, grain size a	nd structure of materials;
CASING INSTALLED: Threaded Welded	and show thickness and nature of each stratum	
35 ft. Gage .250	with at least one entry for each change of forma in position of Static Water Level as drilling proc	-
ft. Gage ft. Gage	- MATERIAL	From To SWL
ft. Gage ft. com	Top Soil	0 3
A DEDECOR A MICONG	Soft Brown Sandy Clay	3 7
PERFORATIONS: Perforated? Yes No.	Cememted Sand & Gravel	
Type of perforator used TorchX Mills		
Size of perforations $1/2$ in. by 6 in.	Sand & Gravel Sand Gravel & Clay	18 27 27 29
138 perforations from 18'6" ft. to 33' 6" ft.	Cemented S nd & Gravel	
perforations from ft. to ft.	Cemented 5 nd & Graver	27 35
ft. to ft.		
perforations from ft. to ft.		
perforations from		
(7) SCDEENS.		
(7) SCREENS: Well screen installed? ☐ Yes Ā No		
Manufacturer's Name		
Type Model No.		
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
(8) WATER LEVEL: Completed well.		
Static level 16'6" ft. below land surface Date 8-2-67		
Aresian pressure lbs. per square inch Date		
(9) WELL TESTS: Drawdown is amount water level is		
lowered below static level		
Was a pump test made? ☐ Yes X☐ No If yes, by whom?	Work started 8-1-67 19 Complete	1 8-3-67 19
Yield: gal./min. with ft. drawdown after hrs.		-3-67 ₁₉
<u>" </u>	Drilling Machine Operator's Certification:	
Bailer test 300 gal./min. with 2ft. drawdown after 1 hrs.	This well was constructed under my dir rials used and information reported above	ect supervision. Mate-
Artesian flow g.p.m. Date	knowledge and belief.	
Temperature of water Was a chemical analysis made? ☐ Yes ☐ No	[Signed] Elwood B. Nanderson I	Date 8-10, 1967
(10) CONSTRUCTION:	Duilling Machine Operators 2	1.30
Well seal—Material used Bentonite Clay	Drilling Machine Operator's License No. 4	<u> </u>
Depth of sealft.	Water Well Contractor's Certification:	
Diameter of well bore to bottom of seal 10 in.	This well was drilled under my jurisdic	
Were any loose strata cemented off? Yes No Depth	true to the best of my knowledge and belief.	
Was a drive shoe used? ☑ Yes ☐ No	NAME Casey Jones Well Drilling Co Inc (Person, firm or corporation) (Type or print)	
Did any strata contain unusable water? Yes No		
Type of water? depth of strata	Address Oute 8 Box 695 Pleasant Hill	
Method of sealing strata off	[Signed] Halbert of Jones	
Was well gravel packed? Tyes To Size of gravel:	(Water Well Contract	or)
Gravel placed from ft. to ft.	Contractor's License No. 103 Date	8-10-67 19