JUN 10 1966 WATER WELL REPORT

· <u>/_</u>		10/2	
State Well	Ño.	15/5W-11	K

NOTICE TO WATER WELL CONTRACTOR

The original and first copy JUN 10 1966 WATER WELL REPO
filed with the STATE ENGINEER, SALEM, OREGON 7810 ENGINEER TATE OF OREGON
within 30 days from the date A | EM OREGON (Please type or print)

G-3905

State Permit No. .

of well completion.			
(1) OWNER:	(11) WELL TESTS: Drawdown is amount we lowered below static lev	ater level	is
Name Bob Nixon	Was a pump test made? Yes No If yes, by whom		
Address Star Route, Junction City, Oregon	Yield: gal./min. with ft. drawdown		hrs.
Address Otal Rodge, Odirodzon Ozoję Ozogon	" " " "	- urter	"
(2) LOCATION OF WELL:	" " "		"
(2) LOCATION OF WELLS:	Bailer test 4000 gal, h.Rn. with 22 ft. drawdow	wn after	l hrs
County Lane Denton Driller's well number	Artesian flow g.p.m. Date	, <u> </u>	
1/4 1/4 Section // T. 15-5 R. 5-W W.M.	Temperature of water Was a chemical analysis m	 nade? □ Yo	es 🛪 No
Bearing and distance from section or subdivision corner	(40) THEFT TOO		8"
		ing	
	Depth drilled 56 ft. Depth of completed well	1 56	ft
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each ch	and struct re materia ange of fo	ture, and I in each ormation
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	THE LITTLE CO.	210017	
N=w Well X Deepening ☐ Reconditioning ☐ Abandon ☐			
andonment, describe material and procedure in Item 12.	top soil	0	1
	sandy clay	-	8
(4) PROPOSED USE (check): (5) TYPE OF WELL:	sand clay gravel	8	14
Domestic 🍪 Industrial 🗌 Municipal 📋 Rotary 🗍 Driven 🖂	brown gravel		24
Irrigation ☐ Test Well 🗷 Other ☐ Dug ☐ Royad ☐	brown sand gravel		36
Dug Bored	blue sand gravel	36	42
(6) CASING INSTALLED: Threaded Welded	blue sand gravel		56
78 "Diam from 0 ft to 56 ft. Gage •250	Dide Said Glavel	42	- 30
ft. to			
(7) PERFORATIONS: Perforated?-√Z Yes □ No			
T = -			
Type of perforator used Mills Perforator			
Size of perforations 1/4 in. by 3 in. 40			
	-	 	
perforations from ft. to ft.			
perforations from			
perforations from ft. to ft.			-
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes ☒ No Manufacturer's Name			
Model No.		-	-
Dath. Slot size Set from ft. to ft.	Work started 4/28/66 19 Completed 5/2	<u> </u>	
Diam. Slot size Set from ft. to ft.	5 //	2/66 2/66	19
	Date well drilling machine moved off of well 5/2	2/66	19
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal puddle clay & cement	Manufacturer's Name		-
Depth of seal	Type:	,	***************
Diameter of well bore to bottom of sealin.		L-4	
Were any loose strata cemented off? Yes \ No Depth	Water Well Contractor's Certification:	•	
Was a drive shoe used? X Yes \[\] No	This well was drilled under my jurisdiction a	and this r	report
Was well gravel packed? ☐ Yes ☒ No Size of gravel;	true to the best of my knowledge and belief.		
Gravel placed from ft. to ft.	NAME Casey Jones Well Drilling	3 0.	
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type	pe or print)	
Type of water? depth of strata	Address Rt. 2, Box 695, Creswell,	Oregon	1
Method of sealing strata off		_	
	Drilling Machine Operator's License No360	2	
(10) WATER LEVELS:	Isimod Dollast of Lanon		
Static level 8 ft. below land surface Date 5/2/66	[Signed] (Water Well Contractor)	*************	************
Artesian pressure lbs. per square inch Date	Contractor's License No. 103 Date 5/12/66		. 19
	1 Commonour of Procession and annual part in the first the state of th		.,