NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date

WATER WELD GEFORT

STATE OF OREGON

(Please type or print)

(Do not write above this line) of well completion.

(1) OWNER:	(10) LOCATION OF WELL:
Name Hosanna.s Children Center	County Lane Driller's well number
Address P.O. Box 26	14 14 Section 17 T.17s R. 02w W.M.
Springfield , Oregon	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 🖔 Deepening 🗌 Reconditioning 🗋 Abandon 🗎	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 55 ft.
Rotary Driven Domestic Industrial Municipal	Static level 6" ft. below land surface. Date 11/12/70
Crie Jetted I Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded 20	(12) WELL LOG: Diameter of well below casing
6 "Diam from +2 ft. to 27 ft. Gage • 250	Depth drilled 100 ft. Depth of completed well 100 ft.
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
(6) PERFORATIONS: Perforated? ☐ Yes ☑ No.	position of Static Water Level and indicate principal water-bearing strata.
'ype of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Soil & Clay & Boulders 0 20
perforations from ft. to ft.	Grey Sandstone hard 20 45
perforations from ft. to ft.	Blue Sandstone 45 55 6"
perforations from ft. to ft.	Lt. Sandstone 55 100
(7) SCREENS: Well screen installed? [7] Yes (2) No	
(1) SCREENS: Well screen installed? ☐ Yes ② No Manufacturer's Name	
Type Model No.	100' - 4" P.V.C. Liner
Diam. Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(2) WELL TESTS. Drawdown is amount water level is	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
s a pump test made? Yes No If yes, by whom?	370
Yeld: gal./min. with ft. drawdown after hrs.	B1 7. 4 (101)
Air_ Test	WINTER RESOURCES DEPT
"	SALEM, OREGON -
gal./min. with 100 ft. drawdown after 1 hrs.	
tesian flow g.p.m.	
Temperature of water Depth artesian flow encountered ft.	Work started 11/12 19 79 Completed 11/12 1979
CONCERNICATION	Date well drilling machine moved off of well 11/12 1979
well seal—Material used Cement Grout	
OF .	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	
Number of sacks of cement used in well seal6sacks	(Drilling Machine Operator)
How was cement grout placed?	Drilling Machine Operator's License No386
Pressure Pumped	Victor Vivil Contractor's Contification
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? \square Yes $ ot No$ Plugs Size: location ft.	Name Pitcher Pump & Drilling Co.
Did any strata contain unusable water? Yes I No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 87829 Greenh 11 Road Eugene, Oregon 97402
Method of sealing strata off	[Signed] Cas lately
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. V494 Date 11/27 1979