

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT
STATE OF OREGON
SEP 20 1978
(Do not write above this line)
WATER RESOURCES DEPT.

LANE

State Well No.

State Permit No.

185/4W-5
60891
LANE 16870

(1) OWNER:

Name Heckman (Heckman Investments)
Address 1505 Juhl St.
Eugene, Ore 97402

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒

6" Diam. from 1.6 ft. to 2.0 ft. Gage 250-w
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations	in.	by	in.
..... perforations from	ft.	to	ft.
..... perforations from	ft.	to	ft.
..... perforations from	ft.	to	ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.

" " " " " "

Bailer test No water gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement Grout
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
How was cement grout placed?
Drilled with Drill Equipment

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lane Driller's well number
1/4 1/4 Section 5 T18-S R. 4-W W.M.

Bearing and distance from section or subdivision corner

Parcel 4400—Code area no. 4-15
Lot ONE—Block 2—Willow Co Estates

(11) WATER LEVEL: Completed well.

Depth at which water was first found no water to ft.

Static level no water ft. below land surface. Date 8/31/78

Artesian pressure lbs. per square inch. Date 8/31/78

(12) WELL LOG:

Diameter of well below casing 6 inch

Depth drilled 145 ft. Depth of completed well 70 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brown Sandy Clay	0	4.4	FT.
" " "	4	14	"
Blue " "	14	50	"
Blue Clay Stone	50	76	"
Gray Clay Stone	76	95	"
Gray Clay Stone	95	145	"

Work started 8/29 1978 Completed 8/31 1978

Date well drilling machine moved off of well 8/31 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Floyd E. Godinier Date 8/31, 1978
(Drilling Machine Operator)

Drilling Machine Operator's License No. 512

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name C. E. Godinier & Son
(Person, firm or corporation) (Type or print)

Address 1941 Harris St Eugene, Ore

[Signed] Floyd E. Godinier
(Water Well Contractor)

Contractor's License No. 895 Date 8/31, 1978