LANE 66985

STATE OF OREGON WATER SUPPLY WELL REPORT

(as required by ORS 537.765)

WELL I.D. # L 88051

START CARD # <u>186575</u>

Instructions for completing this report are on the last page of this form.	
Name BRIVE KEIS CAAROBEA	(9) LOCATION OF WELL (legal description)
Address 105 SUNSHIPE ACKES	County
City Fugene, State OR Zip 97401	Township 195 Nor S Range 2W E or W WM
City 209	Section 29 NE 1/4 VE 1/4
(2) TYPE OF WORK New Well	
☐ Deepening ☐ Alteration (repair/recondition) ☐ Abandonment ☐ Conversion	Lato'" or (degrees or decimal) Longo'" or (degrees or decimal)
(3) DRILL METHOD Rotary Air Rotary Mud Cable Auger Cable Mud	Street Address of Well (or nearest address) 82140 BEAN CL Rd
Other	aresuell, 012.
Otilei	
(4) PROPOSED USE	(10) STATIC WATER LEVEL ft. below land surface. Date
Domestic Community Industrial Irrigation	ft. below land surface. Date /0/14/06
☐ Thermal ☐ Injection ☐ Livestock ☐ Other	ft. below land surface. Date
(5) BORE HOLE CONSTRUCTION Special Construction: Yes No	Artesian pressure lb. per square inch Date
Depth of Completed Wellft.	(41) WATER READING TONES
Explosives used: Yes No Type Amount	(11) WATER BEARING ZONES Depth at which water was first found
BORE HOLE SEAL	
Diameter From To, Material From To, Sacks or Pounds	From To Estimated Flow Rate SWL
10. 0 19 BENT. 0 19 BEACES	
7/2' 19 59	
5/2" 59 67	
How was seal placed: Method	(12) WELL LOG Ground Elevation
Backfill placed fromft. toft. Material	1 -
Backfill placed fromft. toft. Material	FOREST TOBOIL 1 3
Graver praced from tr. to tr. Size of graver	CKAY-BEOWN WI Kroken CS 3 12
(6) CASING/LINER	1345HL7, 12 25
Diameter From To, Gauge Steel Plastic Welded Threaded	BASHLT WILLARDS OF GRAVEL 25 55 BASHLT GRAVEL 55 67 53'
Casing: 6" +1 59 250 & 12	BASALT GRAVEL 55 67 53'
Casing: 47 47 59 235 & 12 12 13 14 15 15 15 15 15 15 15	
	RECEIVED
Liner: 4" -4 67' CLID 🗖	
	NOV 1 3 2006
Drive Shoe used Inside Outside None Final location of shoe(s)	WATER RESOURCES DEPT
Final location of shoe(s) 59' 6(5/z")	SALEM, OREGON
(7) PERFORATIONS/SCREENS	OALLIVI, OTEGOT
Perforations Method 5KIII SUL	
Screens Type Material	to large to the second
	Date Started 10/25/06 Completed 10/26/66
From To Slot Number Diameter Tele/pipe Casing Liner Size size	(unbonded) Water Well Constructor Certification
	I certify that the work I performed on the construction, deepening, alteration, or
47 6) 6* 50 96 9*	abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to
	the best of my knowledge and belief.
—— ———————————————————————————————————	
	WWC Number Date
(8) WELL TESTS: Minimum testing time is 1 hour	Signed
☐ Pump ☐ Bailer ☑ Air ☐ Flowing Artesian	Signed
Yield gal/min Drawdown Drill stem at Time	(bonded) Water Well Constructor Certification
B GOH 14' 67 1 HR.	I accept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates reported
	above. All work performed during this time is in compliance with Oregon water
Temperature of water Depth Artesian Flow Found	supply well construction standards. This report is true to the best of my knowledge
Was a water analysis done? Yes By whom	and belief.
Did any strata contain water not suitable for intended use?	WWC Number
Salty Muddy Odor Colored Other	1.11
Depth of strata:	Signed With Fall