## NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

o not write above this line)

LANE 6828 State Well No. 14 No.

State Permit No. .....

(1) OWNER:	(11) LOCATION OF WELL:
Name Jee Mentgemery - S.R.S., bex 235	County Lane Driller's well number #358
Address Yachats, Oregon 97498	14 14 Section 27 T.15S R. 12W W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	North 90 east 13 feet to Northwest corne
New Well   ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	ef cabin #15
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing
Rotary Driven Domestic M Industrial Municipal Domestic M Industrial Municipal Domestic	Depth drilled 90 ft. Depth of completed well 90 ft.
Dug	Formation: Describe color, texture, grain size and structure of materials;
CASING INSTALLED: Threaded Welded To the Diam from 16" ft. to 82 8 8 ft. Gage 250	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.
ft. Gageft. Gage	MATERIAL From To SWL
	dark brewn clay, seme a*
PERFORATIONS: Perforated?   Yes X No.	sand, gravel and beulders 8
	brewn clay, gravel and " 8 22
Type of perforator used	dark brown clay and some 22
Size of perforations in. by in.	gravel 46
perforations from	hard lava reck 46 49
perforations fromft. toft.	dark, medium hard sandstene 49 51
perforations from ft. to ft.	water bearing 434 46 dark medium hard sandstene 31 59
	dark grey sand, gravel 59
pertorations from	and lightend grey clay 70
(7) SCREENS: Well screen installed?   Yes  No	dark grey lava reck 70 80
Manufacturer's Name	" cearse sand and 80dark/grey/
Type Model No	fine gravel 90
Diam Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WATER LEVEL: Completed well.	
Static level 34½ ft. below land surface Date 8/22/69	
sian pressure	
(9) WELL TESTS: Drawdown is amount water level is	
Was a pump test made? ☐ Yes ♣ No If yes, by whom?	
Yield: 15 gal./min. with 16½ ft. drawdown after 1 hrs.	Work started 8-6 1969 Completed 8-23 1969
" " "	Date well drilling machine moved off of well 8 = 23 1960
" " " "	Drilling Machine Operator's Certification:
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best
Artesian flow g.p.m. Date	knowledge and sclief.
Temperature of water 50 Was a chemical analysis made? ☐ Yes 🖫 No	[Signed] Share Quellow Date 8-29 , 19.69
(10) CONSTRUCTION:	Drilling Machine Operator's License No. 163
Well seal-Material used bentenite & concret	
Depth of seal 2 to 22 ft.	Water Well Contractor's Certification:
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Were any loose strata cemented off? Tyes   No Depth	NAME Charles Panschew, Rte. 1, bex 192
Was a drive shoe used? ☑ Yes □ No	(Person, firm or corporation) (Type or print)
Did any strata contain unusable water?   Yes   No	Address Flerence, Oregon 97439
Type of water? depth of strata	l A P
Method of sealing strata off	[Signed] Mabel Tanschow
Was well gravel packed? ☐ Yes ☐No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 87 Date 8-29 , 1969.