NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

LANE 6984

WATER WELL REPORT

STATE OF OREGON
(Please type or print)
(Do not write above this line)

LANE 6984

State Well No. 16S/1W-33C

State Permit No.

RECEIVED
JUN 16 1978
WATER RESOURCES DEPT.
SALEM, OREGON

(1) OWNER:

Name Jim Cobb
Address 2679 Kincaid Eugene Ore.

(2) TYPE OF WORK (check):

New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [ ] Driven [ ]
Cable [X] Jetted [ ]
Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [X] Industrial [ ] Municipal [ ]
Irrigation [ ] Test Well [ ] Other [ ]

(5) CASING INSTALLED:

Threaded [ ] Welded [X]

6" Diam. from +1 ft. to 47 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? [ ] Yes [X] No.

Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [ ] Yes [X] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [ ] Yes [X] No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "

Bailer test 1½ gal./min. with 400 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement Grout
Well sealed from land surface to 47 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 12 sacks
How was cement grout placed? placed in hole & pudded in with Drill Tools

Was a drive shoe used? [ ] Yes [X] No Plugs Size: location ft.
Did any strata contain unusable water? [ ] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [ ] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Lane Driller's well number
¼ S W ¼ Section 33 T. 16 S R. 1-W W.M.
Bearing and distance from section or subdivision corner
Map 1601
Tax lot 2900

(11) WATER LEVEL: Completed well.

Depth at which water was first found 50 ft.
Static level 28 ft. below land surface. Date 6-5-78
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"
Depth drilled 420 ft. Depth of completed well 420 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Red Clay	0	20	
Soft Brown clay + Sand	20	40	
Blue Sandstone	40	420	

Work started 5/27 1978 Completed 6-5 1978
Date well drilling machine moved off of well 6-5-78

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Garland Cox (Drilling Machine Operator) Date 6-5-, 1978

Drilling Machine Operator's License No. 512

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name C. E. Gardinier & Son (Person, firm or corporation) (Type or print)
Address 1941 Harris St Eugene Ore.
[Signed] Lloyd E. Gardinier (Water Well Contractor)
Contractor's License No. 295 Date 6/5, 1978

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119