NOTICE TO WATER WELL CONTRACTOR OF The original and first copy of this report are to be filed with the APR 14 1972 STATE OF ORIGINAL

APR 14 1972 STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 27810 ENGINEER type or print) within 30 days from the date of well completion. SALEM OR. (Do not write above this E SALEM OR. (Do not write above this line) State Well No.

State Permit No.

(本) OWNER:	(10) LOCATION OF WELL:		
Name WILLAME TANS INC	County LANE' Driller's well number		
Address PO BOX 1054 EUBENE 97401	1/4 1/4 Section / 5 T. /60 R. 2 W W.M.		
	Bearing and distance from section or subdivision	corner	
(2) TYPE OF WORK (check):			
New Well Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(4) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 19 ft.		
Rotary Driven Domestic M Industrial Municipal Domestic	Static level 35 ft. below land sur	face Date 12.	21-71
Cable Jetted Dug Bored Irrigation Test Well Other			
	Artesian pressure ins. per square i	nen. Date	
CASING INSTALLED: Threaded Welded Welded Frame Frame	Depth drilled 90 ft. Depth of complete		8/ ft.
	Formation: Describe color, texture, grain size and		
ft. toft. Gage	and show thickness and nature of each stratum	and aquifer per	netrated,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation position of Static Water Level and indicate princip		
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	RED CLAY W/ROULDERS	0 17	
	TED C-KAY WITHGENIAS		
perforations fromft. toft.	RED CIAY	17 60	
perforations fromft. toft.	7-37		
	RED CLAY W/ WEATHERD)		
Well screen installed? Yes No		60 80	
Manufacturer's Name			
Type Model No.	WEATHERED GRAVEL		
Diam. Slot size Set from ft.	LIN CLAY	80 90	
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	WEATHERET) OPILE!		-
Was a pump test made? Yes No If yes, by whom?	CALINA BELOW CASING		
	CAN THE DESCRIPTION OF THE PROPERTY OF THE PRO		
Yield: gal./min. with ft. drawdown after hrs.	E. W. L. W. W. C.		
	was a second of the second of		
11 - 4 -			
Bailer test 40 gal./min. with 20 ft. drawdown after / hrs.			
Artesian flow g.p.m.			1 80
nperature of water Depth artesian flow encountered ft.	Work started /2 -/5 19// Completed	12-21	197/
(49) CONSTRUCTION:	Date well drilling machine moved off of well	12-21	1971
Well seal-Material used CEMEN, T	Drilling Machine Operator's Certification:		
Well sealed from land surface to 60 ft.	This well was constructed under my d Materials used and information reported at		
Diameter of well bore to bottom of seal 95k + in.	best knowledge and Medies.		
Diameter of well bore below seal in 91/	[Signed] [Signed] [Signed] Day	ate 12.21	, 19.7%
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.		
Number of sacks of bentonite used in well seal sacks	Drining Watchine Operator's Excense 190	f	
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdict		eport is
of waterlbs./100 gals. Was a drive shoe used? May Yes □ No Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water? Yes No	Name MAN (Person, firm or corporation) (Type or print)		
	Address NT2 BOX 438 C E	UC ENE 9	
Type of water? depth of strata Method of sealing strata off	111. 111.		
	[Signed] ///And / (Water Well Contract	tor	
Was well gravel packed? Yes No Size of gravel:	67	-21	71
Gravel placed from ft. to ft.	Contractor's License No. 7 / Date	<i>K</i>	., 19.4