RECEIVED STATE OF OREGON WATER WELL REPORT AUG 2 3 1985 (as required by ORS 537.765) WATER RESOURCES DEPT	$(N^{\gamma} \Lambda 5^{\circ})$	165/3W-		
(1) OWNER: CALEM, OREGON Name Bob Meltebeke Paradise Homes Address 3324 Regent	(10) LOCATION OF WELL by legal description: County Lane <u>4 NW 4 of Section 35</u> of Township 16S Barra 3W W			
City Eugene State Oregon	1000000000000000000000000000000000000	(Township is North or South) (Range is East or West) Tax Lot 202 Lot Block Subdivision		
(2) TYPE OF WORK (check):	Tax Lot Lot Block Subdivision MAILING ADDRESS OF WELL (or nearest address)			
New Well 🔀 Deepening 🗆 Reconditioning 🗆 Abandon 🗆 If abandonment, describe material and procedure in Item 12.	Country View H Coburg, Oregon			
(3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary Air IX Driven Domestic Domestic Industrial Municipal Industrial Rotary Mud Dug Irrigation Withdrawal Rotary Mud Bored Piezometric Grounding Test Integration	(11) WATER LEVEL of COMPLETED WELL: Depth at which water was first found 108 ft. Static level 30 ft. below land surface. Date 8 / 9 / 85 Artesian pressure lbs. per square inch. Date			
(5) CASING INSTALLED: Steel Threaded H Plastic Threaded H Velded 250 " Diam. fromft. toft. Gauge	(12) WELLLOG: Diameter of well below casing6 '' Depth drilled 140 ft. Depth of completed well 140 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
Threaded Welded	MATERIAL	From To	SWL	
<u>4½</u> "Diam. from <u>-20</u> ft. to <u>140</u> ft. Gauge <u>188</u>	Top Soil	0 12		
(6) PERFORATIONS: Perforated? Yes I No	Bar Run Gravel	12 26 26 45		
Size of perforations $1/4$ in. by 6 in.	<u>Soft Brown Shale</u>	45 60		
	Blue Shale	60 140	30'	
(7) SCREENS: Well screen installed? Yes K No				
Manufacturer's Name				
Type Model No. Diam. Slot Size Set from ft. to			·	
Diam. Slot Size Set from ft. to Diam. Slot Size Set from ft. to			, · ·	
Main: Slot Size Set from ft. to ft. (8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? Yes XXNo If yes, by whom?			 I	
d: gal./min. with ft. drawdown after hrs.				
Air test 35 gal/min. with drill stem at 135 ft. 1 hrs.				
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
Depth artesian flow encountered ft.	Date work started 8 / 6 / 8 5/completed_	8/9/	/85	
(9) CONSTRUCTION: Special standards: Yes D No 🕅	Date work started 8 / 6 / 8 3/completed Date well drilling machine moved off of well	8/9/ 8/9/		
wen sear-material used	(unbonded) Water Well Constructor Certificati		· · · · · · · · · · · · · · · · · · ·	
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and			
Diameter of well bore to below seal $\frac{6}{100000000000000000000000000000000000$	information reported above are true to my best know	/ledge and belief.		
Amount of sealing material Method "C" sacks F pounds D	[Signed]			
How was cement grout placed :	(bonded) Water Well Constructor Certification: Bond 5032206 Issued by: Safeco (number) (Surety Company Name)			
Was pump installed?	On behalf of <u>Carter's</u> Drilling (type or print name of Water	& Pump S	Service	
Was a drive shoe used: In res In No Prings	This well was drilled under my jurisdiction and best of my knowledge and belief:	I this report is tr	rue to the	
Method of sealing strata off	(Signed) James L. Carle			
Was well gravel packed? Yes XNo Size of gravel:	(Water Well Constructor)	,	·····	
Gravel placed from ft. to ft.	(Dated)	8/9/	. 8.5	
NOTICE TO WATER WELL CONSTRUCTOR The original and first copy of this report	WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310	SF	P*46866-690	

are to be filed with the

within 30 days from the date of well completion.