NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

LANE

State Permit No.

of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97810
within 30 days from the date of well completion.

State Well No. 16/3 42-31

The state of the s			
(1) OWNER: 10. 2 CON	(11) WELL TESTS: Drawdown is amount we lowered below static lev	ater level	is
Name Agnes Adair	Was a pump test made? X Yes \(\subseteq \text{No If yes, by whom:} \))rill:
Address Rt. 2 # 385-C	Yield: 475 gal./min. with 55 ft. drawdown	-	hrs.
Coburg, Oregon	" 250 " 15 "	2	2 "
(2) LOCATION OF WELL:	<u>" 300 " 17 "</u>	-	3 "
. ,	Bailer test gal./min. with ft. drawdow	vn after	hrs.
County Lane Driller's well number	Artesian flow g.p.m. Date		
14 14 Section 3/ T. /6 S R. 3 W W.M	Temperature of water Was a chemical analysis m	ade? 🗌 Ye	s □ No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below case	ing	1.0
	-		
	Depth drilled 205 ft. Depth of completed well		ft.
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each characteristics.	ana structi le material ange of fo	ire, and in each rmation.
(a) MADE ON MODIF () 1)	MATERIAL	FROM	TO
(3) TYPE OF WORK (check):	Loam	0	4
Well Deepening Reconditioning Abandon	Gravel- clay- sand		
It abandonment, describe material and procedure in Item 12.	some water (18-35)	4	35
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Brown cemented gravel	35	85
Rotary [] Driven []	Clay, sand-gravel W B(90-95)85	92
Industrial Municipal Cable Jetted Cable Ca	Clay, sand and gravel	92	140
Dug Bored	Clay, dark brown	140	165
(6) CASING INSTALLED: Threaded □ Welded X	Blue clay, sand-gravel	165	178
10." Diam. from	Black sand - pea gravel-wood	178	189
" Diam. fromft. toft. Gage	Blue clay and gravel	189	205
" Diam. from ft. to ft. Gage			
(7) PERFORATIONS: Perforated? Yes \(\square\) No.			
Type of perforator used 1 Mills knife			
Size of perforations 4 in. by 2 in.			
perforations from ft. to ft			
680	.		
perforations from ft. to ft			
perforations from ft. to ft.	.		
ft. to ft	-		
(8) SCREENS: Well screen installed? ☐ Yes ☐ No			
Manufacturer's Name			
Model No.			
Dram Slot size Set from ft. to ft.	2/00//07	10115	
Diam Slot size Set from ft. to ft	work started 2/20/07 19 Completed	77/67	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 3/8	3/67	19
•	(13) PUMP:		
Well seal—Material used in seal	. Manufacturer's Name		
Depth of seal 18 ft. Was a packer used? no	. Type: H	P	
Diameter of well bore to bottom of seal in.			
Were any loose strata cemented off? 🗌 Yes 🦹 No 🛮 Depth	Water Well Contractor's Certification:		
Was a drive shoe used? ♣ Yes □ No	This well was drilled under my jurisdiction as	nd this re	port is
Was well gravel packed? 🗌 Yes 🛣 No 🥏 Size of gravel:	I twin to the heat of wer lenever added and helief		
Gravel placed from ft. to ft.	NAME W. W. Drilling and Pump	Servi	ce -
Did any strata contain unusable water? 🗌 Yes 🧏 No	(Person, firm or corporation) (Type	e or print)	•••••
Type of water? depth of strata	Address 2320 Main Springfie	1a, 0	regor
Method of sealing strata off	Drilling Machine Operator's License No	١.	
(10) WATER LEVELS:	7.1 4 7.1.1	==	
۶ ۲ مارد	[Signed] Walt Wilson		LU
10. Delow land surface Date 1	(Water Well Contractor)		1
Artesian pressure lbs. per square inch Date	Contractor's License No. 268 Date4/28/	67,	19