## STATE OF OREGON

## WATER WELL REPORT (as required by ORS 537.765)

LANE 7691

## APR 1 8 1984

## APK I O 1304

WATER RESOURCES DEPT PLEASE TYPE or PRINT IN INSALEM, OREGON

165/34-35

(for official use only)

(1) OWNER:	(10) LOCATION OF WELL by legal	description:
Name Paradise Homes #2	County Lane 4 4 5	of Section 35 of
Address 3324 Regent	Township 10S , Range (Township is North or South)	Range is East or West) , WM.
City Eugene State Or.	Tax Lot Lot Block Subdivision	talige is East Of West/
(2) TYPE OF WORK (check):		d of Van Dynn
New Well X □ Deepening □ Reconditioning □ Abandon □	Coburg, Or.	
If abandonment, describe material and procedure in Item 12.		. =
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLET	ED WELL:
Rotary Air X Driven Domestic X Industrial Municipal	Depth at which water was first found	110 ft.
Thermal:		and surface. Date 3-22-84
Other:		square inch. Date
Cable Bored Piezometric Grounding Test	(12) WELL LOG: Diameter of well below	6
6 "Diam. from from ft. to ft. Gauge 250 Plastic Welded X		completed well 145 ft. of materials; and show thickness east one entry for each change of
LINER INSTALLED: Steel  Plastic  Hreaded  Welded	MATERIAL	From To SWL
Threaded  Welded  Welded  PVC  PVC	Topsoil & Boulders	0 2
Diam. from	Brown Clay	2 19
(6) PERFORATIONS: Perforated? X Yes □ No	Fractured Gray Brown Cong.	19 31
Size of perforations 1/8 in, by 2 in.	Brown Clay	31 33
650 perforations from 85 ft. to 145 ft.	Gray Claystone	33 45
ft. to , ft.	Brown Gray Green Cong.	45 115
perforations from ft. to ft.	Gray Brown Clay	115 125
(7) SCREENS: Well screen installed?   Yes No	Gray Brown Cong.	125 145
Manufacturer's Name		
TypeModel No.	•	
Diam Slot Size Set from, ft. to ft.		
Diam. Slot Size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		-
Was a pump test made? Yes No If yes, by whom?		
dield: gal./min. with ft. drawdown after hrs.		
Air test 100 gal./min. with drill stem at 145 ft. 1 hrs.		
Air test 100 gal./min. with drill stem at 145 ft. 1 hrs.  Bailer test gal./min. with ft. drawdown after hrs.	7	
1 · · · · · · · · · · · · · · · · · · ·		
Artesian flow g.p.m.  Semperature of water Depth artesian flow encounteredft.		
	Date work started 3-21-84 /complete	
(9) CONSTRUCTION: Special standards: Yes □ No ♥ Well seal_Material used Portland Cement	Date well drilling machine moved off of well	<b>3-</b> 23 19 84
Well seal—Material useu	(unbonded) Water Well Constructor Certification	ation (if applicable):
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and	
Diameter of well bore to bottom of seal	information reported above are true to my best knowledge and belief.	
Ω/I <b>3</b> ¥ —	[Signed] Doll upphy	Date 3-23 19 84
Amount of sealing material sacks pounds How was cement grout placed? pressure grouted		
Trow was cement grout placeu:	(bonded) Water Well Constructor Certification:  Bond 0511452863 Issued by: United Pacific Ins. (Surety Company Name)	
Was pump installed?	On behalf of Casey Jones Well Drilling, Co., Inc.	
Was a drive shoe used? X Yes No Plugs Size: location ft.	(type or print name of Water Well Constructor)	
Did any strata contain unusable water?   Yes  No	This well was drilled under my jurisdiction a	nd this report is true to the
Type of Water? depth of strata	best of my knowledge and belief:	
Method of sealing strata off	(Signed) (Water Well Constructor)	
Was well gravel packed?  Yes  No Size of gravel:	(Dated) (Water Well Constructor)	
Gravel placed from ft. to ft.	(Daver)	