NOTICE TO WATER WELL CONTRACTOR

water resources department, Salem, Oregon 97310 within 30 days from the date of well completion.

EC EVATER WELL REGARD E IVED ANE State Wall No. State Wall No. NOV 16 19 Hease type or print) RESOURCES DEPT. Permit No.

WATER RESOURCES DEPT	SALEM, OREGON			
(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:	-		
Name Trailer Town (RW)	County Lane Driller's well no	ımber 30	22-22	<u>)</u> .
Address 93520 Highway 99	14 N.W. Section 5 T. 16		ЦW	W.M.
Junction City, Oregon	Bearing and distance from section or subdivisi	: - 		
(2) TYPE OF WORK (check):	Bearing and distance from Section of Subdivisi	on corner		
New Well Deepening Reconditioning Abandon		*		
If abandonment, describe material and procedure in Item 12.				
	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 166 ft.			
Rotary Driven Domestic Industrial Municipal Cobbs	Static level 20 ft. below land surface. Date 9/114/77			
Cable Z. Jetted	Artesian pressure lbs. per squar		-	
CASING INSTALLED: Threaded Welded Welded Threaded Welded Threaded Welded Threaded Threaded Threaded Threaded Welded Threaded Thr	(12) WELL LOG: Diameter of well below casing -0-			
6-5/8" Diam from 164 ft to 169 ft Gage •250	Depth drilled 194 ft. Depth of compl	eted well		ft.
6-5/8" Diam from 189 ft to 194 ft Gage .250	Formation: Describe color, texture, grain size			
Training to the state of the st	and show thickness and nature of each stratu with at least one entry for each change of forma			
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin			
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	Top Soil	0	9	
	Sand & Gravel	9	77	
perforations fromft. toft.	Gravel	17	22	
perforations from ft. to ft.	Sand & Clay	22	28	
perforations from ft, to ft.	Gravel, Sand , Blue Clay	28	20	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Gravel - Clay Cemented	32	16	
Manufacturer's Name JOHNSON	Red Clay	46	40	
Cmaruraa Cmpp	Sand	55	58 58	
Type STATNLESS STEEL Model No. Diam. 8" Telest size 40 Set from 169 ft. to 189 ft.	Blue Clay	58	77),	
Diam. Slot size Set from ft. to ft.	Blue Clay - Red Sand	11)	115	
	Blue Clay	115	161	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Clean Sand - Fine Gravel	164	169	20
∵	Sand	165	186	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	Sand - Clay	180	185	
Held: gal./min. with ft. drawdown after hrs.	Course Sand	185	189	20
Ji u u	Blue Clay	189	194	
n · n · n · n · n · n · n · n · n · n ·				
Bailer test 40 gal./min. with 1 ft. drawdown after 2 hrs.				
Artesian flow g.p.m.	===	1		
emperature of water 52 Depth artesian flow encountered	A 7	ed 10/1	11/	1977
	Date well drilling machine moved off of well	10/1	: : :	1977
(9) CONSTRUCTION: Portland Type 3 Gement				
Well seal—Material used	Drilling Machine Operator's Certification: This well was constructed under my		gunar	vicion
Well sealed from land surface toft.	Materials used and information reported			
Diameter of well bore to bottom of sealin.	best knowledge and belief.	7.0	711.7	. 77
Diameter of well bore below seal in.	[Signed] Date 10/14/, 1977			
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 390			
How was cement grout placed? Pumped From Bottom Up	Drilling Machine Operator's License 140.			
THE REPORT OF THE PARTY OF THE	Water Well Contractor's Certification:			.e
	This well was drilled under my jurisd		d this r	eport is
Was a drive shoe used? KKYes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water? Yes No	Name Carter's Drilling & Pump Service (Type, or print)			
	P.O. How life Springfield American 97177			
Type of water? depth of strata	Address 1.0. DOX 40-001 1181 1519 101 901 71411			
Method of sealing strata off	[Signed] MALLA a a	Mu	1	
Was well gravel packed? Yes Mo Size of gravel:	(Water Well Cont		, .	
Gravel placed from ft. to ft.	Contractor's License No. 126 Date	10/14	<u>/</u>	, 19[7